

# Roofing nails



Roofing screws with washer also called roofing nails, screws nails. It consists of three parts, which are washer, rubber and screws nails.



**Application:** Used for building construction, decoration field, bicycle parts, wooden furniture, electrical component, household and so on.

Roofing Screws With Washer Features:

- \* Length is from the point to the underside of the head.
- \* Umbrella head is attractive and high strength.
- \* Rubber/plastic washer for additional stability & adhesion.
- \* Twist ring shanks offer excellent withdrawal resistance.
- \* Various corrosion coatings for durability.
- \* Complete styles, gauges and sizes are available.

Specification	Length(mm)	Rod Diameter (mm)	Head Diameter (mm)
BWG8*2"	50.8	4.19	20
BWG8*2-1/2"	63.5	4.19	20
BWG9*1-1/2"	38.0	3.73	20
BWG9*2-1/2"	63.5	3.73	20
BWG9*3"	76.2	3.73	20
BWG10*1-3/4"	44.5	3.37	20
BWG10*2"	50.8	3.37	20
BWG10*2-1/2"	63.5	3.37	20
BWG11*1-1/2"	38.0	3.02	18
BWG11*1-3/4"	44.5	3.02	18
BWG11*2"	50.8	3.02	18
BWG11*2-1/2"	63.5	3.02	18
BWG12*1-1/2"	38	2.74	18
BWG12*1-3/4"	44.5	2.74	18
BWG13*1-1/2"	38.0	2.38	15
BWG13*2"	50.8	2.38	15
BWG14*1-3/4"	40.0	2.10	14