CF-C236-6LXX INDUSTRIAL CONTROL SERVER



parameter

1. Intel LGA 1151 6/7/8/9th Gen CPU
2. Support VGA
3. 4*DIMM DDR4 ECC
4. 6*Intel I210 Gigabit Ethernet
5. 2*SATA3.0 1*MINI-SATA
6. 2*PCI-E network card slot
7. 2*USB3.0 1*SIM
8. Size: 430*445*88mm

CHARACTERISTIC

Application scenarios:

Community operators, small and medium-sized enterprises, Internet cafes, hotels, etc
Hardware for soft routing, firewall, gateway, behavior management, UTM, sdwan, VPN, IPTV, AC controller, web monitoring, etc

Host characteristics:

C236 series is a 2U rack type multi network port network security platform product, with modular network card ports, replaceable gigabit network ports and 10 Gigabit optical ports, and supports Intel Core / Xeon series CPUs; High speed reaction, safety and reliability, 7 * 24 hours stable operation.

SPECIFICATIONS

MODEL	6-port industrial computer
CPU	Intel LGA 1151 6/7/8/9th Gen CORE CPU & Xeon series CPU
CHIPSET	Intel C236
RAM	4*DIMM DDR4 ECC max to 64G
STORAGE	2*SATA3.0 1*MINI-SATA
PCI-E	1*MINI-PCIE 2*PCI-E X8 network card slot
I/O	2*USB3.0 1*VGA
NETWORK	6*I210 Gigabit Ethernet (Network card module can be added)
MANAGE	1*RJ45 COM
FAN	2*case fan 1*CPU fan
POWER	550W ATX redundant power supply
SIZE	430mm*445mm*88mm
ENVIRONMENT	-10~60℃ 0%~95% Relative humidity, non condensing
OS	Support ikuai、ROS、Openwrt、Panabit、Linux、Windows etc.X86 system

CF-C236-6LXX INDUSTRIAL CONTROL SERVER

DETAIL





430mm*445mm*88mm 2U rack type



2*PCI-E X8 network card slot



Redundant power supply

NETWORK CARD



4*I350 Gigabit Ethernet



4*I350 SFP Gigabit Ethernet



2*X710 SFP+ 10 Gigabit Ethernet



8*I350 Gigabit Ethernet



8*I350 SFP Gigabit Ethernet



4*X710 SFP+ 10 Gigabit Ethernet