




GAO SU DA TECHNOLOGY CO.,LTD

Add: 5th Floor ,Building A , No.15 Venture Industrial Zone ,Songgang Street, Bao an District ,ShenZhen ,China
M: 86- 13570680992, Web: www.globalsources.com/gsd.tv ; Email : rainbow@justallwin.com

PICTURE



Size	GSD-LG656600 (2KDLED)	GSD-LG656600 (2KDLED)
Panel	BOE、INNOLUX、LG	BOE、INNOLUX、LG
Chassis Solution (主板方案)	CULTRAVIEW: TP.MS3663S.PC821	CVTE: TP.SK516S.PC821
FACTORY MODEL (工厂型号)	GSD-6522	GSD-6522
Resolution (分辨率)	1920*1080	1920*1080
Brightness (整机亮度)	300±10%	300±10%
Aspect Ratio (屏比例)	16:9	16:9
ATV SYSTEM (ATV 系统)		
TUNER RECEIVING RANGE (TV 接收频率范围)	48.25MHz ~ 863.25MHz	48.25MHz ~ 863.25MHz
INPUT IMPEDANCE (输入阻抗)	75Ω	75Ω
VIDEO SYSTEM (图像制式)	PAL, SECAM,NTSC	PAL, SECAM,NTSC
SOUND SYSTEM (伴音制式)	BG, DK, I, L/L',MN, NICAM/A2	BG, DK, I, L/L',MN, NICAM/A2
Max Storage Channels最大存台数	99CH	99CH
DTV SYSTEM (DTV 系统)		
Channel bandwidth (频道带宽)	T/T2/C(44MHz - 862MHz) S2(950MHz - 2150MHz)	VHF (50MHz ~ 230MHz) UHF (474MHz ~ 862MHz)
INPUT IMPEDANCE (输入阻抗)	75Ω	75Ω
Modulation (调制方式)	DVB-T : QPSK,16QAM,64QAM DVB-T2: QPSK,16QAM,64QAM,256QAM DVB-C: 16QAM, 32QAM, 64QAM, 128QAM, 256QAM DVB-S: 8PSK,QPSK,16APSK,32APSK	DVB-T : QPSK,16QAM,64QAM DVB-T2: QPSK,16QAM,64QAM,256QAM DVB-C: 16QAM, 32QAM, 64QAM, 128QAM, 256QAM DVB-S: 8PSK,QPSK,16APSK,32APSK
VIDEO SYSTEM (图像制式)	MPEG-2,MPEG-4,AVC/H.264,H.265	MPEG-2,MPEG-4,AVC/H.264,H.265
SOUND SYSTEM (伴音制式)	MPEG-1,MPEG-2 (layer 1/2),GAAC, Dobby AC3*,Dolby Digital Plus*	MPEG-1,MPEG-2 (layer 1/2),GAAC, Dobby AC3*,Dolby Digital Plus*
Max Storage Channels最大存台数	700CH(DVB-T+DVB-C) 无限制 No Limit(DVB-S)	700CH(DVB-T+DVB-C) 无限制 No Limit(DVB-S)
CONNECTORS (连接端口)		
CABLE/ANTENNA INPUT (RF) (天线)	X2	X2
HDMI INPUT (HDMI 输入)	X3(480i, 480p, 576i,576p, 720p, 1080i, 1080p,4Kx2k@30Hz)	X3(480i, 480p, 576i,576p, 720p, 1080i, 1080p,4Kx2k@30Hz)
15-PIN D-SUB INPUT (VGA) (电脑接口输入)	X1	NO
COMPONENT VIDEO INPUT (高清分量/YPBPR)	X1(Mini)YPbPr	X1(Mini)YPbPr
AV INPUT (AV输入)	X1 (PAL/NTSC/SECAM)	X1 (PAL/NTSC/SECAM)
MINI AV OUT (AV输出)	NO	NO
SCART INPUT(SCART输入)	NO	NO
CI (CI卡输入)	X1	X1
PC AUDIO INPUT (PC音频输入)	X1	NO
EARPHONE (耳机输出)	X1	NO
COAXIAL (同轴)	X1	X1
USB INPUT (USB输入)	X2	X2
TF CARD	NO	NO
RJ45 IN	NO	NO
WiFi	NO	NO
PICTURE (图像)		
COMB FILTER (梳状滤波器)	3D	3D
DE-INTERLACE (隔行扫描)	3D	3D
NOISE REDUCTION (降噪)	YES	YES
PICTURE CONTROL(BRIGHTNESS) (图像控制)	Yes	Yes
USER SELECTABLE PICTURE CONTROL(图像模式)	Yes	Yes
SOUND (声音)		
AV STEREO (AV立体声)	Yes	Yes
TONE CONTROL(BASS/TREBLE) (高低音控制)	Yes	Yes
USER SELECTABLE SOUND CONTROL(声音模式)	Yes	Yes
SPEAKER CONSUMPTION(伴音功率)	2*10W speakers	2*10W speakers
SMART TV		
OS	NO	Android11(AOSP)
CPU	NO	MT9256AAATAB
DDR SIZE	NO	1G
eMMC Flash	NO	8G
OTHER FEATHERS (其他)		

OSD LANGUAGES (OSD语言)	English, French, German, Italian, Spanish, Portuguese (optional)	English,Vietnamese,Thai,Arabic,Russian,Malaysia, Turkish,French(optional)
SLEEP TIMER (睡眠定时)	Yes	Yes
AUTO POWER OFF (自动关机)	YES	YES
V-CHIP (N制) (级别锁)	NO	NO
TELETEXT / (图文)	Yes	Yes
NICAM/(丽音/)	Yes	Yes
AC3	Yes	Yes
USB SUPPORT FILE FORMAT (USB支持视频格式)	mpg/avi/ts/mov/mkv.dat/mp4/vob/rm/rmvb	mpg/avi/ts/mov/mkv.dat/mp4/vob/rm/rmvb
USB SUPPORT FILE FORMAT (USB支持音频格式)	ADPCM,LPCM /MP3 /MPEG1 Layer1,2 /AC3 AAC,HE-AAC /WMA7,WMA8,WMA9 STD CDDA(*.wav) /RealAudio8 LBR DD51 /DDPlus /DTS(Need for apply KEY)	ADPCM,LPCM /MP3 /MPEG1 Layer1,2 /AC3 AAC,HE-AAC /WMA7,WMA8,WMA9 STD CDDA(*.wav) /RealAudio8 LBR DD51 /DDPlus /DTS(Need for apply KEY)
USB SUPPORT FILE FORMAT (USB支持图片格式)	JPEG 8192x8192 Progressive JPEG 1024x768 BMP 3000x3000 PNG 3000x3000	JPEG 8192x8192 Progressive JPEG 1024x768 BMP 3000x3000 PNG 3000x3000
POWER (电源)		
POWER SUPPLY (电源输入范围)	AC 100V~240V 50/60 Hz	AC 100V~240V 50/60 Hz
POWER CONSUMPTION (整机电源功率)	≦ 138w	≦ 138w
STAND BY POWER CONSUMPTION(待机功率)	≦ 0.5w	≦ 0.5w
STAND (底座)	Plastic	Plastic
DIMENSION (纸箱尺寸)	1587*124*963mm	1587*124*963mm
NET WEIGHT (净重)	20.8 KG	20.8 KG
NET WEIGHT (毛重)	26.0 KG	26.0 KG
40HQ (装柜数量)	264	264

无边框款式

