



#### Features:

1. Adopted with Linear slider, so all the three axes (X, Y, and Z) can do fine tuning and quick orientation with perfect positioning accuracy and speedily maneuverability
2. Equipped with touch panel interface and PLC controlling to ensure it work stably and reliably. And it can storage multiple temperature profiling data of users. With password protection and modification function while power on. The temperature profiles will be displayed on the touch screen
3. Three temperature zones to heat up independently, hot air heat up between up and down zones, IR heat in the bottom, temperature precise control is in  $\pm 3^{\circ}\text{C}$ . The upper temperature zone can be moved freely according to needs, the second zone can be adjusted up and down. The top and bottom heaters can be set several segments control at the same time. IR heating zone can be adjusted output power in the light of operation requirements.
4. The hot air nozzle can be rotated in 360 degree, the IR heater in the bottom can heat up the PCB board uniformly.
5. High accuracy K-type thermocouple closed-loop controlling. It can test temperature accurately through external temperature measurement interface, PCB board positioned by closed V-shape slot. The flexible and convenient universal jigs can prevent any damage or PCB deformation as well as it is suitable for all size of BGA package.
6. Large power fan to cool down the PCB quickly. The built-in vacuum pump and external vacuum nozzle is able to take BGA chips out easily.
7. Having alarm prompt function after welding is done, specially added early warning function for convenient operation.
8. It has Passed CE certificate. It is equipped with emergency stop switch and protection equipment to power off automatically when abnormal accident happened. Under this situation that temperature is out of control, circuit can automatically cut off the power with double over temperature protection function.



## Technology Parameters

Total Power	4800W
Upper Heating Power	800W
Lower Heating Power	Second zone:1200W, Third zone: IR 2700W
Power Supply	AC 220V±10% 50/60HZ
Overall Dimension	L605*W600*H520mm
Locating Mode	V-shape card slot, PCB holder can be adjustable by X and Y axes with universal jigs.
Temperature Controlling	K-type thermocouple closed loop control, independent temperature control, precision up to ±3 degree
PCB Size (Max)	370*310mm
PCB Size( Min )	20*20mm
Electrical Material	High sensitive temperature control module,Touch Screen made-in Taiwan
Weight of machine	30KG