

Model			YSAF-09CRDN1	YSAF-12CRDN1	YSAF-18CRDN1	YSAF-12CRDN1-B	YSAF-18CRDN1-B	YSAF-21CRDN1
Power supply		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	9000	12000	17000	12000	18000	21000
	Input	W	824	1170	1660	1172	1954	2050
	Rated current	A	3.58	5.1	7.2	5.10	8.50	8.9
	EER	W/W	3.2	3.01	3	3.0	2.7	3
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	GMCC	GMCC	GMCC	GMCC
Indoor unit	Dimension(W*D*H)	mm	715x194x285	805x194x285	957x213x302	805x194x285	957x213x302	1040x220x327
	Packing (W*D*H)	mm	780x270x360	870x270x360	1035x295x380	870x270x360	1035x295x380	1120x405x310
	Net/Gross weight	Kg	6.9/8.9	8.2/10.4	10.6/13.6	7.4/9.6	10/13	13.8/17.3
Outdoor noise level		dB(A)	55.7	53.5	54	54.5	58.4	54.5
Outdoor unit	Dimension(W*D*H)	mm	700x275x550	700x275x550	770x300x555	700x275x550	770x300x555	845x363x702
	Packing (W*D*H)	mm	815x325x615	815x325x615	900x348x615	815x325x615	900x345x585	965x395x765
	With Pipe - Packing (W*D*H)		815x350x615	815x350x615	910x380x615	815x350x615	910x380x605	985x435x760
	Net/Gross weight	Kg	21.3/23.5	20.5/22.9	27.7/30.1	21.4/23.6	27.2/29.6	38.7/42
Operation temperature		℃	17-30	17~30	17~30	17-30	17-30	17~30
Room temperature	Indoor(cooling/ heating)	℃	17-32/0-30	17~32/	17~32/	17-32/0-30	17-32/0-30	17~32/
	Outdoor(cooling/heating)	℃	18-43/-7-24	0~50/	0~50/	18-43/-7-24	18-43/-7-24	0~50/
Application area (Cooling Standard)		m2	12-18	16-23	23-33	16-23	24-35	28-41
Qty'per 20' /40' /40'HQ			118/250/285	110/227/244	86/180/208	115/240/270	92/200/224	64/136/146