

B. Machine Parameters:

Kneader mixer	X(S)N-5	X(S)N-20	X(S)N-35	X(S)N-55	X(S)N-75	X(S)N-95	X(S)N-110
Mixing capacity (L)	5	20	35	55	75	95	110
Actuating motor (kw)	7.5	37	55	55/75	90/110	132	160/200
Turnover motor(kw)	0.75	1.5	2.2	3.0	4.0	5.5	5.5
Turnover angle (°)	110	110	140	140	140	140	140
Air compressor motor (kw)	1.5	3.0	5.5	7.5	11.0	15.0	15.0
Dust cleaner	HLL-10	HLL-10	HLL-10	HLL-15	HLL-20	HLL-30	HLL-30
Water cooling(Rubber refining) Mpa	0.2-0.4	0.2-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4
Steam heating(Plastic refining) Mpa	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8
Electrical heating(Plastic refining) KW	4	9	12	15	18	24	24
Weight (kg)	1200	4500	6500	7800	10500	12500	14500
Dimension (LXWXH) (mm)	1900x950 x2400	2600x1400 x2600	3200x1900 x3000	3500x2600 x3300	3900x2900 x3400	4000x3200 x3700	4100x2900 x3800