

Product	Model Name/机型名称	26B2F-E
Display/显示部分	Panel Size(diagonal)/尺寸	25.7"
	Panel Type/面板类型	ADS
	Panel Source/面板厂商	BOE
	Panel P/N/面板型号	MV257VUB-N10
	Flat/ Curve/平面/曲面	Flat
	Radius of curvature/曲率	NA
	Aspect Ratio/长宽比	21: 9
	HDR support/HDR支持	NA
	Resolution/分辨率	2560*1080
	Bezel Type/边框类型	frameless bezel
	Display Viewing Area(H*V) (mm)/可视区域尺寸	601.3*253.7mm
	Panel Backlight Type/背光类型 (单侧发光/双侧/直下式)	Unilateral luminescence
	Display Surface(non-glare/ glare)显示表面 (反光/不反光)	non-glare
	Color Saturation (NTSC)色彩饱和度 (NTSC)	CIE1976 105%(Typ.)
	Color Saturation (DCI-P3)色彩饱和度 (DCI-P3)	CIE1976 88%(Typ.)
	Color Saturation (sRGB)色彩饱和度 (SRGB)	CIE1976 99%(Typ.)
	Color Saturation (Adobe RGB)色彩饱和度 (Adobe RGB)	CIE1976 88%(Typ.)
	Pixel Pitch (H)*(V) (mm)屏幕像素点间距	0.2349 (H) ×0.2349(V)
	Brightness (nits)(Max.)背光最大亮度 (典型值) (最小值)	300nit(Typ.),250nit(Min.)
	Contrast Ratio (Typ.)对比度 (最大)	1000:1
	Dynamic Contrast Ratio动态对比度	MILLION
	View Angle(H/V)视角	178/178
	Panel bit depth 屏幕色深	6-bit (Hi-FRC)
	Display Colors显示色彩	16.7M
	Panel Response Time w/o OD	14ms(typ.)
	Response Time 响应时间 OD	7.5ms
	Panel Refresh Rate (Max.) 屏刷新率 (最大)	75HZ
	Display Refresh Rate (Max.) 整机刷新率 (最大)	75HZ
Major Chip/主要的芯片	Scaler PN 方案芯片型号	91A4
I/O	HDMI 1.4	1
	FreeSync Range	2560x1080 75Hz
	HDMI 2.0	1
	FreeSync Range	2560x1080 75Hz
	DP 1.2	1
	FreeSync Range	2560x1080 75Hz
	DP 1.4	/
	FreeSync Range	
	VGA	/
	DVI	/
	FreeSync Range	
	Audio out	1
	USB- type A V2.0/USB 2.0	/
	USB- type A Version-下行接口	/
	USB- type B Version-上行接口	/
	USB- type B QTY/数量	/
	USB- type A QTY/数量	/
	USB- type C Version/Type-c 版本	/
	USB- type C QTY/数量	/
	USB- typc C Function /Type-c 功能	/
	USB charge /USB 充电	/
	Power Delivery/输出功率 (充电协议)	36W
	Speaker/喇叭规格	4Ω3W (real4Ω2W)
Mechanical Design	Display Stand Design /支架ID	Adjustable stand
	Tilt(angle)俯仰角度	-5°-- 20°
	Swivel(angle)左右转动	45°/left/right
	Pivot(angle/direction) 竖屏旋转	90°
	Height Adjustment 高度调整	120mm
	VESA Mount 壁挂规格	100*100mm
	Power Button 电源开关	Y

	OSD Button OSD开关	Y
	Back cover RGB Design 后壳RGB灯效设计	N/A
	Stand RGB Design 支架RGB灯效设计	N/A
	Kensington lock 防盗锁	N/A
Power/电源	Power Consumption电源功耗	Typ. 30W, Max.40W
	Power Saving Mode省电模式	<0.5W
	Power Off Mode关机模式	<0.3W
	Power Type	Adapter
	Power Supply	DC12V,3.0A
Dimension/尺寸	Phys. Dimension with Stand(W*H*D)(mm)	620.4*490.3*230.1
	Phys. Dimension w/o stand (WxHxD)(mm)	620.4*284.9*55.8
	Box Dimension (WxHxD)(mm)	757*417*208mm
Weight	Net Weight (kg)	3.3 (no stand) 5.2 (with stand)
	Gross Weight (kg)	7.5
Packing	Carton (Color or Brown Box) 纸箱 (彩箱/普通牛卡箱)	723*208*428mm——Buckle box
	QSG 使用指南/说明书	
	Warranty card 保修卡	
	Feature label 功能标签	
	Engery label 能效标签	
Container Load/装箱数 理	20' (Q'ty)/ with pallets	260PCS/1300*900*120mm pallte
	40' GP (Q'ty)/with pallets	572PCS/1300*900*120mm pallte
	40' HQ (Q'ty)/with pallets	704PCS/1300*900*120mm pallte
	40' HQ -AU(Q'ty)/with pallets	N/A
软件	1. Color temperature (cold color, warm color, user)	Yes
	2. Low blue light control eye protection	Yes
	3. Profile	Yes
	4. DCR	Yes
	5. Language Menu	Yes [23 langs]
	6. No flicker backlight adjustment	Yes
	7. FreeSync(Adaptive Sync/Freesync /Freesync Premium、Freesync	Yes [48-75Hz]
	8. Over Drive	Yes
	9.FPS/RTS游戏模式一键切换	Yes
	10. GAME PLUS	Yes
	11.PIP/PBP	Yes
	12. PQ setting	N/A
	13.HDR(HDR Ready/HDR 400/HDR 600/HDR1000)	N/A
	14.IR control (optional)	N/A
	15.Ambient light sensor/环境光感应	N/A