

Coaxial to Toslink Audio Converter

Quick Installation Guide Ver. 1.0

All brand names and trademarks are properties of their respective owners

INTRODUCTION:

This Converter enables a coaxial audio signal to be converted to Toslink Digital Audio, for Home Theater Surround Sound Applications or Computer Musical Systems.

This converter supports both PCM and Bitstream signals. These do not decode the audio signal just convert between the electrical signal and the optical signal. They support all decode formats that the respective interface supports.

FEATURES:

- Supports coaxial to Toslink conversion
- Supports up to Dolby Digital or DTS 5.1
- Sample Rates: 44.1 kHz/ 48kHz / 96 kHz/ 192kHz
- Small size
- Easy installation

PACKAGE CONTENTS:

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- 1) 1 x Coaxial to Toslink Audio Converter
- 2) 1 x Power Adapter
- 3) 1 x USB Power Cable
- 4) 1 x User manual

CONNECTION DIAGRAM:



SPECIFICATIONS:

Supported sampling rates	44.1 kHz/ 48kHz / 96 kHz/ 192kHz
Resolution	up to 24 bit
Permissible temperature range	0 to +40 °C
Permissible relative humidity	20 to 90%
Power supply	5 V/DC

Note: Specifications are subject to change without notice.