

Specification	
Model Number	VTS30-G-F
DSP	KM01N-C
Operating system	Android, IOS
APP:	V380 PRO
Sensor:	1/3" Progressive Scan CMOS (SC2337X*3)
Video compressed format:	H.265/12fps
Resolution:	1920*3240P
4G Network :	4G-BAND1/3/5/8/38/39/40/41
Detection method:	PIR + Radar dual induction detection
Detection distance:	0~12M
Detection angle:	120°
Alarm method:	Double induction confirmation and push alarm information mobilephone
Pan-tilt:	Big PTZ: Horizontal: 355 °, vertical: 90°, Small PTZ: Horizontal: 180°, vertical: 90°
Rotate speed	Horizontal 55°/seconds, vertical 40°/seconds
IR Leds	Small PTZs: 6pcs Dual Core LED+ Big PTZ: 8pcs Dual Core LED
Full color night vision:	minimum illumination 0.00001LUX
Infrared Led:	Infrared LED distance: 30M ,effective distance :10M
White Led:	White LED distance: 30M, effective distance :10M
Built-in speaker:	3W
Built-in microphone:	Audio pick-up eara about 20M
Lens:	fixed-focus 4mm+4mm+4mm
Angle:	80°+80°+80°
Cloud storage:	Cloud Storage (Alarm video)
Local storage:	TF card (Max 128G)
power supply mode :	solar panel + 3.7V 18650 battery
Solar panel power:	8W
Battery capacity	Built-in 8000mah battery
Operating power	daytime: 350-400ma,Night time:500-550ma
Standby power	5 mA
work environment:	IP66 Waterproof,can use indoor and outdoor
Working temperature:	-30°~+50°



Working humidity:	0%~80%RH
Color box	26.3*18.8*17.5cm
Carton size	55*40*56cm
Carton quantity	12pcs.
Weight	20.4KG



E

