

Display Size	21.5inch framless Gaming Monitor	21.5inch framless Gaming Monitor	23.8inch framless Gaming Monitor	27inch framless Gaming flat Monitor	27inch framless Gaming flat Monitor	34inch framless Gaming Curved 1800R Monitor
Free SYNC/GSYNC	without Free SYNC & GSYNC	without Free SYNC & GSYNC	with Free SYNC & GSYNC	with Free SYNC & GSYNC	with Free SYNC & GSYNC	with Free SYNC & GSYNC
Photo						
Panel Brand	AUO/BOE/CSOT	AUO/BOE/CSOT	AUO/BOE/CSOT	AUO/BOE/CSOT	AUO/BOE/CSOT	AUO/BOE/CSOT
Resolution	1920(H)×1080 (V) @120Hz	1920(H)×1080 (V) @120Hz	1920(H)×1080 (V) @120Hz	1920(H)×1080 (V) @120Hz	2560×1440 (V) @100Hz	3440(H)×1440 (V) @/180hz
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	21:9
Pixel Pitch	0.0831*0.241mm	0.0831*0.241mm	273.9 (per one triad) x273.9um	311.4 (per one triad) x311.4um	311.4 (per one triad) x311.4um	311.4 (per one triad) x311.4um
Frequency	120Hz	120Hz	120Hz	100Hz	100Hz	120Hz/144hz/180hz
Display Color	16.7M (6-bit + Hi-FRC)	16.7M (6-bit + Hi-FRC)	16.7M (6-bit + Hi-FRC)	16.7M (6-bit + Hi-FRC)	16.7M (6-bit + Hi-FRC)	16.7M (6-bit + Hi-FRC)
Brightness	250-300cd/m² 10+-	250-300cd/m² 10+-	250-300cd/m² 10+-	250-300cd/m² 10+-	250-300cd/m² 10+-	300cd/m² 10+-
Contrast Ratio	IPS 1000:1 (Typ.)	VA 3000: 1 (Typ.)	IPS 1000:1 (Typ.)	IPS 1000:1 (Typ.)	IPS 1000:1 (Typ.)	IPS 4000:1 (Typ.)
Response Time	5-14ms	5-14ms	5-14ms	5-14ms	5-14ms	5-14ms
Viewing Angle	178° (H)/178° (V) (CR ≥ 10)	178° (H)/178° (V) (CR ≥ 10)	178° (H)/178° (V) (CR ≥ 10)	178° (H)/178° (V) (CR ≥ 10)	178° (H)/178° (V) (CR ≥ 10)	178° (H)/178° (V) (CR ≥ 10)
HDMI port	1*HDMI	1*HDMI	1*HDMI	1*HDMI	1*HDMI	2*HDMI
DP port	1*DP	1*DP	1*DP	1*DP	1*DP	2*DP
USB port	N/A	N/A	N/A	N/A	N/A	Optional
Voltage	110-240V 50/60HZ	110-240V 50/60HZ	110-240V 50/60HZ	110-240V 50/60HZ	110-240V 50/60HZ	110-240V 50/60HZ
Consumption	< 36W	< 36W	< 36W	< 36W	< 48W	< 48W
Standby By	< 0.5W	< 0.5W	< 0.5W	< 0.5W	< 0.5W	< 0.5W
Display Area	525.89(W)×295.81(H) mm	525.89(W)×295.81(H) mm	525.89(W)×295.81(H) mm	596.736(W)×335.664(H) mm	596.736(W)×335.664(H) mm	596.736(W)×335.664(H) mm
Relative Humidity	≤80%	≤80%	≤80%	≤80%	≤80%	≤80%
Storage Humidity	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing
Use Humidity	0~50℃	0~50℃	0~50℃	0~50℃	0~50℃	0~50℃

VESA Mounting	N/A	N/A	N/A	N/A	N/A	N/A
Front Control	Five keys mode:Menu, +, -, ,AUTO, POWER	Five keys mode:Menu, +, -, ,AUTO, POWER	Five keys mode:Menu, +, -, ,AUTO, POWER	Five keys mode:Menu, +, -, ,AUTO, POWER	Five keys mode:Menu, +, -, ,AUTO, POWER	Five keys mode:Menu, +, -, ,AUTO, POWER
Adapter	DC12V/3A Wall /Desktop plug optional	DC12V/3A Wall /Desktop plug optional	DC12V/3A Wall /Desktop plug optional	DC12V/3A Wall /Desktop plug optional	DC12V/3A Wall /Desktop plug optional	DC12V/3A Wall /Desktop plug optional
VGA Cable	N/A	N/A	N/A	N/A	N/A	N/A
HDMI Cable	Yes	Yes	Yes	Yes	Yes	Yes
Speaker	NO	NO	NO	NO	NO	NO
User Manual	YES	YES	YES	YES	YES	YES
Warranty card	YES	YES	YES	YES	YES	YES
Reliability	MTBF≥30000H	MTBF≥30000H	MTBF≥30000H	MTBF≥30000H	MTBF≥30000H	MTBF≥30000H
Annual Failure rates	≤1.0%	≤1.0%	≤1.0%	≤1.0%	≤1.0%	≤1.0%
Warranty	12 Months	12 Months	12 Months	12 Months	12 Months	12 Months
Color box Packing size(W*D*H)	56*9*31.5cm	56*9*31.5cm	59.5*38.5*11.8cm	68.5*12*44.5cm	68.5*12*44.5cm	68.5*12*44.5cm
Outer Carton Packing Size(W*D*H)	57*48*32cm (5pcs)	57*48*32cm (5pcs)	60.5*60.5*40cm (5pcs)	71*40.5*45.5cm (3pcs)	71*40.5*45.5cm (3pcs)	71*40.5*45.5cm (3pcs)
20TF	1360pcs	1360pcs	960pcs	640pcs	640pcs	425pcs
40HQ	3300pcs	3300pcs	2350pcs	1590pcs	1590pcs	1111pcs
Gross weight/PC	3.1KG	3.1KG	3.58KG	4.97KG	4.97KG	5.6KG