



P.C.B LAYOUT
BOTTOM VIEW
P.C.B Tolerance ±0.1

USB Connector Termination Assignment

CONTACT NUMBER	SIGNAL NAME
1,5	VBUS
2,6	D-
3,7	D+
4,8	GND
SHELL	SHIELD

NO	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
6	SHIELD	2	BRASS	Ni, t=0.3mm
5	CONTACTS(DIN)	6	COPPER ALLOY	GOLD 3-5µ" AT CONTACT AREA LEAD FREE TIN ALLOY AT TERMINATION, NICKEL OVER ALL.
4	CONTACTS(USB)	8	COPPER ALLOY	GOLD 3-5µ" AT CONTACT AREA LEAD FREE TIN ALLOY AT TERMINATION, NICKEL OVER ALL.
3	COVER	1	P. B. T	BLACK
2	HOUSING(DIN)	1	P. B. T	Purple (PAN 2715C)
1	HOUSING(USB)	1	P. B. T	BLACK

MDUB-FR-06AA-LF
LEADFREE
RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MDUB-FR-06AA

DWG NO. MDUB-FR-06AA

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

FILE NO.

DRAWING BY

.X ±
.XX ±
.XXX ±
AWG

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

