

Display: LCD Display with Backlight, 6000 counts
Operating Environment: 600V CAT IV and 1000V CAT III
DC Voltage Range: 600mV/6V/60V/600V/1000V
DC Voltage Resolution: 0.1mV/1mV/10mV/100mV/1V
AC Voltage Range: 6V/60V/600V/750V
AC Voltage Resolution: 1mV/10mV/100mV/1V
DC Current Range: 600μA/6mA/60mA/600mA/20.00A
DC Current Resolution: 0.01μA/0.01mA/0.1mA/10mA
AC Current Range: 60mA/600mA/20A
AC Current Resolution: 0.01mA/0.1mA/10mA
Frequency Range:
9.999Hz/99.99Hz/999.9Hz/9.999KHz/99.99KHz/999.9KHz/9.999MHz
Frequency Resolution:
0.001Hz/0.01Hz/0.1Hz/0.001KHz/0.01KHz/0.1KHz/0.001MHz
Resistance Range: 600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ
Resistance Resolution: 0.1Ω/1Ω/10Ω/100Ω/1kΩ/10kΩ
Capacitance Range:
9.999nF/99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/99.99mF
Capacitance Resolution:
0.001nF/0.01nF/0.1nF/1nF/10nF/100nF/0.1μF/0.001mF
Duty Cycle: 1%~99%
RPM (Tach): 60~12000RPM

DWELL ANGLE: 2CYL~8CYL

PULSE WIDTH: 1.0 ~ 10.0ms

Fuse: 800mA/20A

Diode Test: ✓

Continuity Buzzer: ✓

Data Hold: ✓

Back Light: ✓

Auto Power Off: ✓

°C/°F: ✓

True RMS: ✓

Data Hold MAX/MIN: ✓

USB connect PC: ✓

Working Temperature/Humidity: 0~40°C; <80%RH

Storage Temperature/Humidity: -10~60°C; <70%RH

Power Supply: 9V(6F22)*1(not included)

Item Size: 166*88*51mm

Item Weight: 320g