

		Winstars Product Specifications		Version	A0
				Page	1/1
		Model	WS-UHP3404M	Date	2017-07-01
		Name	USB3.1 Type-C Mini Dock for Retina Macbook	Writer	
Picture tupia 图片			Features: 特点		
			1. Aluminum designed fit to plug into USB-C port Retina Macbook . Upper USB-C port extended up to five connectivity, including USB3.1 (Power Delivery) upstream power charging 2. Build in one more HDMI V1.4 (4K@30Hz) through USB3.1 (VESA Alternate Mode) video output support 4K resolutions 3. Two USB-A ports extended USB3.0 (5Gbps) data transferring, and USB2.0 compliance 4. USB3.0 SD and TF / Micro SD Card Reader to fill up Retina Macbook missing function 5. One USB-C port extended USB3.1 Gen.1 (5Gbps) data transfer or USB3.1 (Power Delivery) upstream power charging 6. Build in Billboard function		
Title 标题					
USB3.1 Type-C Mini Dock for Retina Macbook					
Description 介绍			Package content 标配	SYSTEM REQUIREMENT: 系统配置	
Aluminum slim design on the Retina MacBook to deliver multi ports in the smallest footprint. HDMI port through USB3.1 VESA Alt. Mode support 4K resolution to present dual UHD 4K display. Additions of 2 x USB3.0-A Hub; 1 x USB3.0 SD / TF Card Reader giving full functionality, one USB-C extended downstream USB3.1 Gen.1 (5Gbps) data transfer or USB3.1 (Power Delivery) upstream power charging. This compact Mini Dock to replace all other dongles be one for portable user. With innovative design, the product have been widely acclaimed by Apple fans.			1. Type-C Mini Dock 2. Leather pouch for product protection	For Retina Macbook 2015 / 2016 or latest version	
Specification 规格					
Hardware 硬件		Functions 功能		Exterior 外观	
Ports	Input: 1 x USB-C, Output: HDMI + 2 x USB-A + 1 x USB-C + HDMI + SD and TF Connector	Working Standards	USB 3.1 Gen1	Color	Apple deep gray
Button	NIL				
LED	Power Indicator Blue				
Chipset	FL5002 + GL3224				
Flash	2M-Bit	Operating System Support	Mac OS		
SDRAM	NIL				
Power Supply	Power from Host Retina Macbook or it's Power				
Power Plug	NIL	Max. Pixels	4K / 30Hz		
Power Consumption	<2Watt	Max. Charing current(A)	NIL		
Rated Voltage/ frequency /current	NIL				
Dimensions 尺寸		Certification 证书			
Unit Dimensions	Size: 134(L) x 41(W) x 9(H)mm	CE-EMC	Enable	NO suitable	
Weight	60g	CE-RTTE	Enable		
Housing Material	Aluminum	CE-LVD	Enable		
Shell color	Apple deep gray	FCC DOC	Enable		
Package Dimension	xx * xx * xx MM (L x W x H) after small PP	FCC ID	Enable		
Environmental 环境		ROHS	Enable		
Operating Temperature	0°C~40°C	Reach	Enable		
Storage Temperature	-10~70°C	3C			
Relative Humidity(Operational)	10%~90%,noncondensing	Others 其他			
Relative Humidity(Storage)	10%~90%,noncondensing	Method	See Manual		
Drop test (1 Meters)	3 st	Performance	See Test Report		
Cycle work (hours)	24Hour	Reliability	See Test Report		