Electrical Parameter:

Camera(s)	
Transmit Frequency Range	2400Mhz~2483.5Mhz
Data Rate	4 Mbps
Transmitting Power	16dBm (TYP)
Modulation Type	GFSK with FHSS
Transmitting Distance	150m (Line of Sight)
Image Sensor Type	1/4” Color CMOS Image Sensor
Effective Pixels	H: 1280 V: 720
Light sensitivity	3.5 Lux /o IR-LEDs)
Image Processing	MPEG-4
Image Resolution / Frame Rate	Cam x 2 : 720px1 @ 15 fps Cam x 2 : VGAx2 @ 30 fps Cam x 4 : QVGAx4 @ 30 fps/VGA x 4 @ 15 fps
Lens	3.6mm / F2.0 (ICR cut Filter)
Viewing Angle (Diagonal)	64° (FOV)
Daylight sensor	<5 Lux (IR On), >30 Lux IR Off
IR LED / Night Vision Range	1 Led / 850nm, 12m (with IR Led)
LED	6pcs 1W/pc white LEDs
Power Requirement	9V DC 600mA ±5%
Power Consumption	1680mA Max (with IR ON and white led on and talk back)
Dimension	232mm*84mm*119mm
Operating Temperature	14°F ~ 104°F (-10°C ~ 40°C)
Protection class	IP54
Operating Humidity	0% ~ 85%