

壁厚表 Wall Thicknesses Scheduel

公称通径 Norminal Pipe Size DN(in.)	外径 Outside Diameter Diameter	公称壁厚表 T Norminal Wall Thickness												
		Sch10	Sch20	Sch30	STD	Sch40	Sch60	XS	Sch80	Sch100	Sch120	Sch140	Sch160	XXS
1/8	10.3	-	-	-	1.73	1.73	-	2.41	2.41	-	-	-	-	-
1/4	13.7	-	-	-	2.24	2.24	-	3.02	3.02	-	-	-	-	-
3/8	17.1	-	-	-	2.31	2.31	-	3.20	3.20	-	-	-	-	-
1/2	21.3	-	-	-	2.77	2.77	-	3.73	3.73	-	-	-	4.78	7.47
3/4	26.7	-	-	-	2.87	2.87	-	3.91	3.91	-	-	-	5.56	7.82
1	33.4	-	-	-	3.38	3.38	-	4.55	4.55	-	-	-	6.35	9.09
1 1/4	42.2	-	-	-	3.56	3.56	-	4.85	4.85	-	-	-	6.35	9.70
1 1/2	48.3	-	-	-	3.68	3.68	-	5.08	5.08	-	-	-	7.14	10.15
2	60.3	-	-	-	3.91	3.91	-	5.54	5.54	-	-	-	8.74	11.07
2 1/2	73.0	-	-	-	5.16	5.16	-	7.01	7.01	-	-	-	9.53	14.02
3	88.9	-	-	-	5.49	5.49	-	7.62	7.62	-	-	-	11.13	15.24
3 1/2	101.6	-	-	-	5.74	5.74	-	8.08	8.08	-	-	-	-	-
4	114.3	-	-	-	6.02	6.02	-	8.56	8.56	-	11.13	-	13.49	17.12
5	141.3	-	-	-	6.55	6.55	-	9.53	9.53	-	12.70	-	15.88	19.05
6	168.3	-	-	-	7.11	7.11	-	10.97	10.97	-	14.27	-	18.26	21.95
8	219.1	-	6.35	7.04	8.18	8.18	10.31	12.70	12.70	15.09	18.26	20.62	23.01	22.23
10	273.1	-	6.35	7.80	9.27	9.27	12.70	12.70	15.09	18.26	21.44	25.40	28.58	25.40
12	323.9	-	6.35	8.38	9.53	10.31	14.27	12.70	17.48	21.44	25.40	28.58	33.32	25.40
14	355.6	6.35	7.92	9.53	9.53	11.13	15.09	12.70	19.05	23.83	27.79	31.75	35.71	-
16	406.4	6.35	7.92	9.53	9.53	12.70	16.66	12.70	21.44	26.19	30.96	36.53	40.49	-
18	457.2	6.35	7.92	11.13	9.53	14.27	19.05	12.70	23.83	29.36	34.93	39.67	45.24	-
20	508.0	6.35	9.53	12.70	9.53	15.09	20.62	12.70	26.19	32.54	38.10	44.45	50.01	-
22	558.8	6.35	9.53	12.70	9.53	-	22.23	12.70	28.58	34.93	41.28	47.63	53.98	-
24	609.6	6.35	9.53	14.27	9.53	17.48	24.61	12.70	30.96	38.89	46.02	52.37	59.54	-
26	660.4	7.92	12.70	-	9.53	-	-	12.70	-	-	-	-	-	-
28	711.2	7.92	12.70	15.88	9.53	-	-	12.70	-	-	-	-	-	-
30	762.0	7.92	12.70	15.88	9.53	-	-	12.70	-	-	-	-	-	-
32	812.8	7.92	12.70	15.88	9.53	17.48	-	12.70	-	-	-	-	-	-
34	863.6	7.92	12.70	15.88	9.53	17.48	-	12.70	-	-	-	-	-	-
36	914.4	7.92	12.70	15.88	9.53	19.05	-	12.70	-	-	-	-	-	-
38	965.2	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-
40	1016.0	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-
42	1066.8	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-
44	1117.6	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-
46	1168.4	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-
48	1219.2	-	-	-	9.53	-	-	12.70	-	-	-	-	-	-

注：Sch5s、10s、40s、80s用于不锈钢管件，已经隐藏