



深圳市星光彩科技有限公司

Shenzhen Xing Guang Cai Technology Co.,Limited

Add: No.2505 Road,Shiyan Town, Baoan District, Shenzhen, China

Contact Person:Ms Helen Qin Skype:helenqin32 Mob/WhatsApp/Wechat: +86 17688933149

Email:sales02@szxgclcd.com

Web: www.xgclcd.com

P10 outdoor LED display parameter

LED Module		
	pixel pitch	10mm
	module size	320*160mm
	module resolution	32*16
	LED	SMD3535
	Scan	1/4scan
	Application	Outdoor
	Weight	0.42KG

LED Cabinet		
	Cabinet Size	960*960mm or customized
	Cabinet resolution	96*96dots
	module quantity	3*6pcs
	LED driver	5V 40A 200W
	Material	Iron
	Receiving card	1pcs

LED Screen				
	Pixel density	10000dots/m ²	Continuous Working Hours	>72 hours
	Ave power consumption	200W/m ²	Using Life	100,000 hours
	Max power consumption	800W/m ²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥10m	Scatter OOC Point	<0.01%
	Brightness(cd/m ²)	≥4500cd	Continuous OOC Point	None
	Refresh Rate	300---2440 frame/s	IP Grade	IP65/IP54
	LED Drive mode	Constant Current	Working Temperature	-35C----+60C
	Display color	1M---69G	Working Humidity	10---90%
	Viewing angle	W140° ,H140°		