

Azvox S940 Nagra3 Twin Tuner

Main Spec: 1, Nagra 3 & Nagra 2+Twin Tuner+FTA+SKS+IKS+Full HD (1080p) 2, WLAN+CA+2 USB-PVR 3, WI-FI+Youtube+CCCAM+NEWCAM+Weather Forecast... 4, WI-FI (WIFI is possible by USB WIFI dongle)	<i>(note: quotation valid in 10 days)</i> FOB ShenZhen usd65-75.00
Feature: Fully DVB-S/DVB-S2/MPEG2/MPEG-4/H.264/AVC Compliant Manual-proof User Interface and Easy-Going Remote Control Twin Tuner PVR, Watching One Channel while Recording another Channel Transportation Stream Recording Supported Multi language OSD Dual USB for Multimedia Player (MP3,MP4,OGG,MKV,JPEG,BMP) News, Map and Weather Applications Via IP Games supported FTA/CAS(1CA) Auto DiSEqC 1.0 and DiSEqC 1.1 /1.2/USALS supported DV OUT Video&Audio Output (576i,576p,720p,1080i,1080p) Unicable and MDU Supported 800 TV&Radio Channels Supported NIT Auto Search, Blind Search, Manual Search, TP Search, and Multi Satellite Search 7 Days EPG (Electronic Program Guide) Easy-going Program Editors, Tele-text and Subtitle Supported PVR Time Shift and Palyback Supported Upgrading Supported by OTA, USB, FTP and Kingofsat Web Data Backup Supported by USB(two USB prot) Low Power Consumption Stanby	Product Photos 
1. Tuner & Channel Demodulator Mode: QPSK,8PSK,16APSK Frequency Range: 950Mhz ~2150Mhz RF Input Connector: F-Female Double tuners	2.Audio: Audio Decoding: MPEG1 layer1/2 , MPEG2 Layer 2. Audio Mode: Mono/Stereo/Left/Right Subtitle Teletext: DVB Subtitle and Teletext Subtitile EBU Teletext
3. Video: (Decoding, output, resolution) Video Decoding: ISO/IEC 11172-2 MPEG1, ISO/IEC 13818-2 MPEG2 MP@HL,ISO/IEC 14496 MPEG4 compliant Support SP@L3 to ASP@L5,ISO/IEC 14496-10 AVC high profile@level 4.1 main profile@level 4.1 Output: CVBS(video format@ 576i or 480 i) YPbPr (video format default@Auto) HDMI 1.3 (video format default @Auto),support HDCP. Video Resolution: 1080p/i 720p/i 576p/i 480p/i Aspect Ratio: 4:3 16:9	4.PVR Function: Record: Watching A Sat Channel While Recording B Sat Channel Instant Record and Timer Record EPG Teletext Timeshif PVR Operation: Descrambled and Scrambled of Programme Record,Support Total TS Stram Record Including EPG, Subtitle, Teletext Support Timeshift on/off Setting in Menu Play/Pause /Stop /Step Fast Forward / Fast Backward 2/4/8/16/24 Farmat Supported PVR Manager: Jumap Step by Step and Length of Step (30secs/1min/5min/10min/30min) Support NTFS&FAT32 Support File Lock ,Delete ,Rename File Information
5. Physical Specification Aspect ratio: 4:3, Letterbox, 16:9, Pan & Scan Operating Temperature: 0 C~40 C Storage Temperature: -20 C ~ 75 C Power: 90 VAC ~ 240 VAC power switch Max 40 Watt	6. Rear Panel IF IN/ IF OUT/ CVBS Connector/Audio CINCH Conector/ Y/Pb/Pr Connector/SCART/USB/ RS232/Ethernet/DV OUT/SPDIF/WIFI antenna/Switch
7. Accessories RCU: IR RC3/ Other on Request (38 kHz) NEC Batteries: 2*aar6 Type Unser Manual: English AV Cable: 1 HDMI Cable: Optical	8.Size/N.W/G.W Size: 240x180x55mm Net Weight: 0.3KG Gross Weight: 0.7KG



SHENZHEN PLUTE HI-TECH HK LTD

Add: Rm901, Baoyunda Communication Building, Qian Jin Avenue, Bao An, ShenZhen, China

Tel: +86-755-81458145ext. 809 Fax: +86-755-81458519 Mob: +86-13510262620

www.plutecom.com

Email: estella@plutecom.com MSN: estella.luo@hotmail.com Skype: [estellaluo](https://www.skype.com/user/estellaluo)

Quotation

Product Name: S2S+ --Nagra3 TV Channels	Stock
Main Spec: DVB-S2 +PATCH(Nagravision2.0+3.0)+Multicas+USB PVR+HDMI 1080P Full HD +LED Display+KS.Biss.Cryptworks(Internet Sharing)	FOB ShenZhen usd48-56.00
HDTV Station -S2 HD Feature:	Product Photos
Supports MPEG-2, MPEG-4, H.264 and fully DVB compliant - DiSEqC 1.0, 1.1, 1.2 and USALS - Aspect ratio adjustment 4:3 (16/9 crop), 4:3 (16/9 letterbox), 16:9 (4/3 pillar box) - User friendly OSD and operation - Total 4,000 Channels Programmable - Multi-language audio support Multi-language menu text support - Favorite channel selections - Parental Guide and rating control - EPG(Provider Electronic Program Guide) for On Screen Channel Information - On-Screen Display with 65,536 Color - Blind scan(Power Scan) & Powerful EPG - Zoom Function in Pause - Dolby Digital Bitstream Out through S/PDIF(Coaxial) - Selectable output for 1080p, 1080i, 720p, 480p and 480i format - Multiple Video Outputs "HDMI, Component(YPbPr), Composit" - USB 2.0 Host (Access to HDD, USB memory, Others etc) : - Upgrade Software & Update Channel Database through USB 2.0 Port and RS232 - MP3 File Play by USB 2.0 - PVR Ready via USB 2.0 - Multimedia file play by USB 2.0	 
HDTV Station -S2 HD Specifications	
1. Tuner & Channel	3. MPEG Transport Stream & A/V Decoding
Type 1 F Type, IEC169-24, Female Frequency Range 950MHz to 2150MHz RF Impedance 75 Ohm unbalanced Signal Level -65 to -25 dBm LNB Power 13/18Vdc +/- 5%, 0.5Amax, Overload Protected 22KHz Tone Frequency :224KHz +/- 2KHz, 0.6Vpp +/- 0.2V DiSEqC Control Version1.0, 1.2, Tone burst A/B Demodulation QPSK, 8PSK Input Symbol Rate DVB-S QPSK : 1~45 Msps DVB-S2 8PSK/QPSK : 10~30Msps FEC Decoder 1/2, 2/3, 3/4, 3/5, 4/5, 5/6, 8/9, 9/10 in DVB-S2 mode. 1/2, 2/3, 3/4, 5/6 and 7/8 in DVB-S mode.	Transport Stream 13818-1 MPEG-2, H.264/AVC Transport stream Specification Profile Level MPEG-2 MP@ML, MP@HL, MPEG-4 H.264/AVC Input Rate Max. 90Mbit/s Aspect Ratio 4:3, 16:9, Letter Box Frame Rate 25Hz for PAL, 30Hz for NTSC Video Resolution 576i, 576p, 720p, 1080i, 1080P Teletext Through VBI Audio Decoding MPEG-1 Layer 1 & 2, Dolby Downmix Audio Mode Single Channel/Dual Channel Joint Stereo/Stereo Frequency Response 20~20kHz, <+/-2dB
2. System & Memory	4. A/V & Date In/Out
Main Processor ALI3606 Flash Memory 4Mbytes DDR II Memory 512Mbytes Channel Capacity Digital Channel: 4,000 Front 1-Key(Power), 7-SEGMENT DISPLAY	HDMI HD Video/Audio Output Data Interface - RS-232, Bit Rate: 115,200baud Connector: 9-pin D-sub Male type - USB : USB 2.0, Type A Connector,
5. Power Supply	6. Physical Specification
Input Voltage AC 100V ~ 240V, 50Hz ~ 60Hz Power AC 100V ~ 240V	Size(WxHxD)53*34*28cm Weight:NT0.98KG/GW1.09KG
7. Environmental Condition	
Operating Temperature 0 °C 40 °C Storage Temperature -10 °C 50 °C Operating Humidity Range 10~85% RH, Non-condensing Storage Humidity Range 5~90% RH, Non-condensing	



SHENZHEN PLUTE HI-TECH HK LTD

Add: Rm901, Baoyunda CoMMunication Building, Qian Jin Avenue, Bao An, ShenZhen, China

Tel: +86-755-81458145#809 Fax: +86-755-81458519 Mob: +86-13510262620

Web: www.plutecom.com; www.mpeg4-dvb-receiver.com

Email: sales4@plutecom.com MSN: plutecom-sales4@hotmail.com Skype: sales4_plute

Product Name: Ibox Dongle

1. Open Nagra3
2. compatible with many receivers(S810B, Azfox S2S, Evo XL etc)
3. Fast S/W update

FOB ShenZhen usd26.00-30.50

Ibox Dongle (PSR935) Feature:

Product Photos

- MPEG-2 Digital and Fully DVB-S Compliant
- SCPC/MCPC receivable from C/KU band Satellite
- User friendly OSD Menu with Full Function
- Installation by Easy Setup Guide
- 100 Satellites, 6000 Channels and 4000 Transponders
- Brilliant On Screen Graphic
- Small Picture in Graphic
- Update Via SDX
- 7 Favorite Groups and Parent Lock Function
- EPG, Including 4 days data fast download and timer
- Supports DiSEqC 1.1/1.2 and 22KHz Tone
- 256 Color Graphic Switching
- Fast Channel Switching
- Super Fast 800 Pages OSD Teletext Supported
- VBI Teletext Supported
- High Sensitivity QPSK Tuner and Demodulator
- Multi Timer Function
- Multi Language
- Support 20 Audio PID (Language)
- RS232 port for Additional Information Service and Upgrading Software
- LNB Power Overload protection
- Letter Box and Pan & Scan



Accessories:

Cable for RSS232 serial
Cable Phone Jack
User Manual
Adapter

Work with Receivers as Below:

Azfox S2S, Azamerica s800, s806, s807, s810, s810b,
Azbox Evo XL, Azbox Evo XS, Azbox Newgen,
Azamerica s900HD, Megabox 1000USB,
Megabox 1000HDMI E E OUTROS.
Azplus HD-200 y CV-100 Etc.

Server:

Amaz-61, Telstar12

Package:

20'/40'/40'HQ: 3500 /6500 /8000 PCS
Gift: 190*142*43mm 0.352kg
Carton: 435*302*220mm 7.55kg

