

SPECIFICATIONS

ITEM / MODEL		YO01T1(BR) /YO01T3(BR)	YO03T1(BR) /YO03T3(BR)	YO06T1(BR) /YO06T3(BR)	YO10T1(BR) /YO10T3(BR)
RATED VOLTAGE		125/250V AC	125/250V AC	125/250V AC	125/250V AC
RATED CURRENT		1A	3A	6A	10A
LEAK CURRENT		0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ	0.8mA MAX 250V,50HZ
TEST VOLTAGE	LINE TO LINE	1450V DC	1450V DC	1450V DC	1450V DC
	LINE TO GROUND	2250V DC	2250V DC	2250V DC	2250V DC
INSULATION RESISTANCE		100M ohm MIN 250VDC	100M ohm MIN 250VDC	100M ohm MIN 250VDC	100M ohm MIN 250VDC
DIRECT CURRENT RESISTANCE		0.5 ohm MAX	0.2 ohm MAX	0.15 ohm MAX	0.1 ohm MAX
TEMPERATURE RISE		30C MAX	30C MAX	30C MAX	30C MAX
OPERATING TEMPERATURE		-25 ~ +85C	-25 ~ +85C	-25 ~ +85C	-25 ~ +85C
CX		0.1uF Max	0.1uF Max	0.1uF Max	0.1uF Max
CY		3300pF Max	3300pF Max	3300pF Max	3300pF Max
R		1M,10M/ohm	1M,10M/ohm	1M,10M/ohm	1M,10M/ohm
INDUCTANCE		3.7mH	1.8mH	0.7mH	0.3mH
ATTENUATION	NORMAL MODE 25dbMIN	0.60 ~ 45MHZ	0.80 ~ 50MHZ	0.80 ~ 50MHZ	1.00 ~ 50MHZ
	COMMON MODE 25dbMIN	0.10 ~ 40MHZ	0.20 ~ 50MHZ	0.40 ~ 50MHZ	1.00 ~ 50MHZ