Model			YWT-18CMN1	YWT-12CMN1
Power supply		Ph-V-Hz	1Ph ,220-240V~,50Hz	1Ph ,220-240V~,50Hz
Cooling	Capacity	Btu/h	18000	12000
	Input	W	1720	1213
	Current	A	7.5	5.7
	EER	W/W	3.07	2.9
Moisture Removal		L/h	1.8	1.2
Rated input consumption		W	2600	1750
Rated current		A	13.5	8.7
Starting current		A	42	28
Compressor	Type		ROTARY	ROTARY
	Brand		HITACHI	RECHI
Indoor side air flow(Hi/Mi/Lo)		m3/h	750/650/550	430/385/340
Indoor side noise level (Hi/Mi/Lo)		dB(A)	57/54/51	51.5/49.5/48.5
Outdoor side noise level (Hi/Mi/Lo)		dB(A)	63/61/59	60.5/59/58
Refrigerant type		kg	R410A/0.69	R410A/0.55
Design pressure		MPa	4.2/1.5	4.2/1.5
Control type			Mechanical Control	Mechanical Control
Operation temp	indoor(cooling/heating)	℃	17-32/---	17-32/---
	outdoor(cooling/heating)	℃	18-43/---	18-43/---
Application area （Cooling Standard)		m^2	24-35	16-23
Dimension(W*D*H)		mm	660x680x428	600x560x380
Packing (W*D*H)		mm	746x815x515	685x620x430
Net/Gross weight		Kg	54.4/58.7	36/39
Loading quantity 20’ /40’ /40'HQ		Pieces	84/180/225	135/285/342