



**深圳市星光彩科技有限公司**  
**Shenzhen Xing Guang Cai Technology Co., Limited**


Add: 2505 Songbai Road, Fenghuang village, Fuyong Town baoan district, Shenzhen, China

Contact Person: Ms Helen Qin Skype: helenqin32 Mob/WhatsApp/Wechat: +86 17688933149


Email: sales02@szxgled.com

Web: [www.xgled.com](http://www.xgled.com)

**P5 Outdoor RGB SMD full color LED Display parameter**

LED Module		
 <p style="text-align: center; font-size: small;">outdoor 320x160 p5 led module</p>	pixel pitch	5mm
	module size	320*160mm
	module resolution	64*32
	LED	SMD2525
	Scan	1/8Scan
	Application	Outdoor
	LED chip	Epistar

LED Cabinet		
	Cabinet Size	960mm (W) *960mm (H)
	Cabinet resolution	192*192dots
	module quantity	3*6=18PCS
	LED driver	G-energy
	Material	Sealed iron
	Receiving card	1PCS

LED Screen				
	Pixel density	40000dots/m <sup>2</sup>	Continuous Working Hours	>72 hours
	Ave power consumption	260W/m <sup>2</sup>	Using Life	100,000 hours
	Max power consumption	900W/m <sup>2</sup>	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥5m	Scatter OOC Point	<0.01%
	Brightness(cd/m <sup>2</sup> )	≥6500cd	Continuous OOC Point	None
	Refresh Rate	300---2440 frame/s	IP Grade	IP65/IP54
	LED Drive mode	Constant Current	Working Temperature	-35C----+60C
	Display color	1M——69G	Working Humidity	10---90%

