

	SoC	ASR1803L CAT4 / SV6158	
	Dimension	108*67*16mm	
	Bands	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)	
	Form factor	MIFI	
	Battery	Li-ion Battery 3700mAh Working time: 7-8 hrs, Standby time: around 350 hrs (Depend on network)	
	Wi-Fi	802.11 b/g/n, WIFI speed up to 150Mbps, max 15 users connection	
	Memory	512Mb RAM	
	Data Rates	LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL	
	Hardware	USB	USB2.0, Type C
		SIM	4FF (eSIM / VSIM optional)
		LED	Battery/WIFI/Signal
		Antenna	Build-in FPC type
		Power Voltage	USB DC 5V
	Software	Button	Reset(Pinhole), Power
		Update	FOTA & Local update
		Support OS	Compatible with Windows / MACOS / Linux / Android IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics,
		Others	WIFI Security
	Operation Temperature	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80%	
		Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%	

Model: L817A



LTE Cat4 ASR1803L Cost effective Solution
eSIM/VSIM support optional