

Basic Functions	Range	Best
-----------------	-------	------

QQ2. 0

DC Current	25mA/250mA	±3%
DC Voltage	0.5V/2.5V/10V/50V	±3%
	250V/500V	
AC Voltage	10V/50V/250V/500V	±5%
Resistor	R×1	±3%
	R×10/R×1k	±10%

360TRx

DC Current	2.5mA/25mA/500mA	±3%
DC Voltage	2.5V/10V/50V/250V/1000V	±3%
AC Voltage	10V/50V/250V/1000V	±4%
Resistor	R×1/R×10	±3%
	R×100/R×1000	±10%

Special Functions	QQ2. 0	360TRx
-------------------	--------	--------

Continuity Buzzer	R<50Ω	√
Low Battery Display		√
Anti-drop Protective Pouches		√
Multi-protective Circuit		√

General Characteristics			
-------------------------	--	--	--

Product Colour		Grey and Yellow	Yellow
Product Net Weight	Approx 135g		
Windows Size	54×44mm	√	
	75×57mm		√
Product Size	110×76×25.5mm	√	
	123×84×34mm		√
Power	2×1.5V 5#		√
	1×1.5V 7#	√	
Standard Accessories	Packing Carton、English Manual、Test Lead		
Standard Packing Quantity		90	60
Standard Packing Carton Size	500×250×275mm	√	
	440×355×275mm		√
Standard Carton Gross Weight		Approx 14kg	Approx11.8kg

