

Brand	Innolux	Model P/N	N116BCA-EA1
Diagonal Size	11.6"	Panel Type	a-Si TFT-LCD, LCM
Resolution	1366(RGB)×768, WXGA 135PPI	Pixel Format	RGB Vertical Stripe
Active Area	256.125(W)×144(H) mm	Bezel Opening	-
Outline Size	278(W)×168(H) ×3(D) mm	Surface	Antiglare, Hard coating (3H)
Brightness	250 cd/m ² (Typ.)	Contrast Ratio	800:1 (Typ.) (TM)
Viewing Angle	89/89/89/89 (Typ.)(CR≥10) ?	Display Mode	AAS, Normally Black, Transmissive ?
Best View on	Symmetry	Response Time	14/11 (Typ.)(Tr/Td)
Display Colors	262K 45% NTSC	Lamp Type	10S2P WLED , 15K hours , With LED Driver
Frequency	60Hz ?	Touch Screen	Without
Shape Style	Slim (PCBA Flat, T≤3.2mm)	Application	
Signal Interface	eDP (1 Lane) , eDP1.2 , 30 pins Connector		
Input Voltage	3.3V (Typ.)		
Environment	Operating Temp.: 0 ~ 50 °C ; Storage Temp.: -20 ~ 60 °C		