

	J23-6.3	J23-10	J23-16	J23-25	J23-40	J23-40A	J23-63	J23-80	J23-100	
nominal force(KN)	63	100	160	250	400	400	630	800	1000	
sliding block stroke(mm)	55	60	70	80	100	120	120	120	130	
number of sliding block stroke(times/minute)	170	145	120	65	50	55	50	50	50	
max closed height(mm)	170	180	220	280	320	220	370	370	390	
closed height adjustment(mm)	30	35	50	50	60	80	80	80	90	
distance from slider block center to the frame(mm)	110	130	160	200	205	250	260	260	300	
length between columns(mm)	150	170	220	250	260	300	350	300	380	
size of table(mm)	left-right	200	240	300	380	380	480	480	580	600
	front-back	310	370	450	650	650	710	710	760	900
hole size for die handle(mm)	diameter	30	30	40	40	50	50	60	60	60
	diphth	55	55	60	60	70	70	70	70	70
tilt angle(degree)	30	30	30	30	20	20	20	20	20	
dimensions(mm)	left-right	780	895	1130	1325	1740	1600	1810	1810	1930
	front-back	600	713	834	990	1040	1180	1350	1350	1380
	height	1537	1668	1890	2140	2100	2310	2740	2740	2790
motor power(KW)	0.75	1.1	1.5	2.2	4	4	5.5	7.5	7.5	