

SHENZHEN HUARUI ELECTRONIC TECHNOLOGY CO., LIMITED

Floor 5,Building B,New Retail Digital Industrial Park,Nanchang Second Industrial Zone,Xixiang Street,
Bao'an District,Shenzhen,Guangdong

Mobile:0086-137 2429 2138 Email:alex@szhret.com Wechat/Skype/Whatsapp:+86 137 2429 2138



H3101 Android desktop pos terminal

CPU	1.8GHZ RK3399 ARM 6 core Cortex- 2*A72+4*A52
Memory DDR	3GB RAM
Operating system	Android 7.1
Flash NAND FLASH	EMMC 8GB
Main screen	TFT 10.1 inches, resolution: 1280X800, display ratio: 16: 9, industrial screen G+G capacitive 5-point touch screen, scratch-resistant, hardened
Secondary screen	TFT 1.9 inches, resolution: 128X64
Physical keyboard	19-digit password keyboard, silicone button
NFC card reader	Mifare 13.56MHZ NFC read and write
QR code scanning camera	2 million pixel HD, two-dimensional code recognition
Face recognition camera (Optional)	1.3 megapixel HD, dedicated for face recognition, with fill light / optional 2-8 million pixels and binocular
Microphone	High sensitivity condenser microphone
Communication part	WIFI module: Execution standard ---- IEEE802.11b/g/n compatible wapi (optional)
	BT: Bluetooth BT4.1LE short-range wireless communication
	Ethernet interface (RJ45) supports common protocols such as TCP/IP HTTP
Printer	Built-in thermal printer, 58MM high speed printing
Case	ABS material pure white
Package	Standard industrial packaging (neutral + cartoon + manual + warranty card)
	Weight: 1.5Kg
Power Adapter	World standard: input 100-240V; output DC9V 3A
External interface	TF deck (maximum 32GB) 1
	SIM card holder 1
	Ethernet interface RJ45 1
	USB socket a total of 3
	Audio input/output socket microphone 1 earphone 1
	DB9 standard serial port 2
	DC power input socket 1 input current 9V 3A
	DC power switch (soft switch) 1
	MINI USB OTG 1
Operating temperature	-10℃ - 50℃
Storage temperature	-40℃ - 80℃