

360 Degree Video Conferencing Camera VCC-308



Features:

- USB2.0 interface,driver-free,plug and play;
- Supports software such as Goodview, CISCO, Vidyio, Skype, Webex, etc;
- Support power-off memory,power-on automatic recovery;
- Support hoisting, landing, wall mounting;
- 80° degree super wide-angle, with full HD lens, no distortion of imaging;
- Stable operation, low noise;
- Support automatic calibration function of preset position, long-time operation without deviation;
- Support all-round remote control reception, not restricted by the installation location;
- Support automatic identification of control protocol, users do not need to set;
- Support wide dynamic function, the use environment is not affected by backlight;
- Support one-key image flip function;
- Support proportional variable speed function, convenient to quickly move to the specified target

Interface:



Parameters:

Model	VCC-THF-308-10X	VCC-THK-308-10X
DSP+Sensor	T31X+SC4335	Mstar+IMX415
Pixels+Frame	2560*1440P/30fps	3840*2160P@30fps
Sensor Brand	SmartSens	SONY
Lens	4.7mm-47mm	
Visual View	Up to 50 Meters	
View Angle	Wide /69.5°~7.95°; Tele /35°~3.97°	
Optical Zoom	10X	
Lens Aperture	F1.8~2.8	
Focus range	0.5M~Infinity	
Focusing	Method:Automatic / Manual	
Wide dynamic	Off/support digital wide dynamic	
Video output	USB 2.0	
Power	DC 12V 2.0 interface	
Control	RS232 (Loop through)	
	RS485(the longest distance can reach 1200 Meters)	
Horizontal	Rotation Range:0~355° Rotation Speed:0.1°~100°	
Vertical	Rotation Range:30~90° Rotation Speed:0.1°~50°	
Proportional	Speed and focal length automatically match	
Materials	ABS	
Functions	Support Mechanical zero calibration	
	Support OSD characters	
	10 Number of preset positions	
	Omni-directional receiving, effective control distance≤10Meters	
Power supply	DC 2V(2A)	
Consumption	≤10W	
Application	Indoor	
	Working humidity:20% ~ 80%	
	Range of working temperature:-15°C ~ +50°C	
	Video conference, remote recruitment, business negotiation, medical consultation, etc.	
System	WinXP/Vista/WIN7/Android/IOS//Linux	
1pcs	1.31KG/160mm×137.5mm×156mm	