

Model	X(S)K-160	X(S)K -250	X(S)K -360	X(S)K -400	X(S)K -450	X(S)K -550	X(S)K-660
Diameter of rolls	160	250	360	400	450	550	660
Working length of roll	320	620	900	1000	1200	1500	2130
Working speed of front roll	8.95	14.9	17.4	19.3	23.1	28.6	30
Fraction ratio of rolls	1:1.35	1:1.1	1:1.27	1:1.27	1:1.27	1:1.29	1:1.05
Max.gap(mm)	5	8	10	10	10	15	15
Nip regulating mode	Manual	Manual	Manual	Manual or Electric	Manual or Electric	Manual or Electric	Electric
Batch capacity(Kg)	1-2	10-15	20-15	25-35	30-50	50-60	120-140
Motor	Power	5.5	15	30	45	55	90/110
	Motor speed(r/m)	1440	730	980	740	980	740
Reducer	Full closed type hardened gear speed reducer						
Reduction ratio	43	35	49.7	38	47.2	35.6	126.2
Overall dimension (mm)	1120x920 X1295	3400x1270 X1620	4140x1770 X1700	4490x1700 X1750	5570x1900 X1750	6290x2330 X1780	7500x 2630x2060
Weight (kg)	1100	4200	7600	9000	11500	20000	26500