

IPC-THS-945

2.0M Black light illumination H.265 IP Camera

Features:

- Supporting human detection and tripping line detection, and supports intelligent functions such as customized face detection, number statistics, etc.
- 1080P HD Black light illumination resolution, clear and fine images;
- Support 2D/3D noise reduction, digital wide dynamic;
- Advanced H.265AI/H.265+ (Compatible with H.265/H.264) video compression, Super low rate, high definition quality of image;
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.
- Support ONVIF; access third party, Support various mobile monitoring (iPhone, Android);
- Provide web、CMS、center platform management software MYEYE, provide SDK development
- Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed

Parameters:

Model	IPC-THS-945
System structure	Embedded RTOS, dual-core 32bit DSP(Hi3516EV200), pure hard compression, watch dog
Sensor	2.0M 1/2.9" IMX307 Black light illumination CMOS sensor, color 0.0001Lux@F1.2, black/white 0.0001Lux@F1.2
Video compression	H.265AI/H.265+ (Compatible with H.265/H.264), support dual stream, AVI; 0.1M~8Mbps variable; 1~30f/s variable
Image output	Main stream: 1920*1080@25fps, 1280*720@25fps; sub-stream: 704*576@25fps;
Shutter	1/50(1/60)s to 1/10,000s
Lens	Built-in Manual 2MP 2.7mm-13.5mm Varifocal Lens(Motorized 2.8-12.0mm Lens Optional)
IR LED	5:30pcs SMT IR LED
IR Distance	IR Effective Distance 30Meters
Day and night	Support IR-CUT
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Audio compression	G.711, support bidirectional talk, audio&video synchronization
Audio interface	Support Microphone & Speaker Ports on Cable or Housing(Optional)
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/DHCP/NTP/UPnP etc
Signal interface	One photo resistance interface, one IR-CUT interface, support photo resistance signal and IR-CUT links to IR
Alarm I/O	1/I (support alarm input and video link to background)
Reliability	Comprehensive lightning protection, 7 * 24 hours -10℃~65℃ high temperature stable and reliable testing
Intelligence analysis	Supporting human detection and tripping line detection, and supports intelligent functions such as customized face detection, number statistics, etc.
Other function	Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software、MYEYE; perfect SDK;
ONVIF	Support 2.42
POE	POE IEEE802.3af/at Supported
Mobile monitoring	Support multiple mobile monitoring (iOS、Android)
Application	Vandal-proof Outdoor(Weatherproof IP66 Standard)
Working Temp.	-30 ° C ~ +65 ° C
Power	DC12V/2A or POE 48V input
Power Consumption	≤3W
Package Dimension	15*15*13CM
Weight	0.8kgs