


2206 SPEC SHEET

2023.1.10

Product Picture		Selling Points	
		◆ 1080P FHD camera, clearly record every detail.	
		◆ Strong cost performance advantage.	
		◆ Support infrared night vision, large-angle infrared lights, and have delicate night vision effects.	
		◆ Two-way intercom, to meet the needs of on-site remote instant communication; echo cancellation, clear and accurate communication between the two parties.	
		◆ Support mobile APP. The on-site situation can be monitored at any time through the mobile phone, and an event or abnormal alarm will be sent immediately when detected.	
		◆ Support motion detection and sound detection.	
		◆ Support local storage. The TF card supports a maximum capacity of 256G, and the local video can store more content and save it for a longer time.	
		◆ H.265 efficient encoding, saving a lot of storage space.	
Product Features			
			
Configurations			
Hardware	SOC	Sigmastar SSC333	
	DDR	512Mbit Built-in	
	Flash	64Mbit	
	OS	Linux	
	NPU	N/A	
	WiFi	Support 2.4G	
	Image Sensor	GC2083, 1/3 inch	
	Pixel Size	2MP	
	Lens instructure	1G+3P	
	Lens Angle	D91.9°H78.3°V42.8	
	Aperture	F2.0	
	Power supply	5V1A charger/constant electricity	
	Network	wifi 2.4G	
	Rotation Angle	PTZ rotation 350° * 67°	
Video	Image Resolution	1080P	
	Frame rate	20fps	
	Encoding Format	H.265	
Detection	Lens	/	
	Trigger angle	N/A	
	Trigger distance	N/A	
Night performance	Infrared night vision Configuration	2pcs 850nm Infrared light	
	Infrared night vision distance	10M	
	Full color night vision Configuration	\	
	Full color night vision distance	\	
Audio	Intercom mode	Full duplex two-way intercom	
	Intercom distance	1-3M	
	Speaker	8Ω1W	
Software	APP	AIOT cam	
	Supported system	IOS/android	
	AI	\	
Storage	Local storage	Support up to 256G TF card	
	Cloud storage	Support	
AI features	Motion detection	Support	
	Sound detection	Support	
Battery / Super Cap	Battery type	/	
	Battery capacity	/	
	Battery life	/	
Accessories	Chime	/	
	AC adapter	5V1A charger	
	USB cable	Mirco USB interface, 1M cable length	
Product size	Product size	104*69*69 mm	
	Product weight	160g	
	Waterproof Level	\	
Others	Operating temperature	-10° ~ +50°	
	Storage temperature	-20° ~ +60°	
	Certificates	FCC/CE/ROHS	