Panel Printer HCC-E3

Feature

1.Easy paper loading
2.Low noise thermal printing
3.Support RS232 or parallel interface
4.Front panel makes paper replacement easily
5.Easily embedded to any kind of instruments and meters

Specification

Printing Method	Thermal Line
Resolution	8 dots/mm, 384 dots/line
Effective Printing Width	48mm
Printing Speed	100mm/s
Character Set	ASCII, GB18030(Chinese), BIG5
Print Font	ANK: 9×24, 12×24
Self-defined Character	Yes
Character Per Line	32
Graphic	Support bitmap downloading
Paper End Sensor	Yes
Power Supply (Adapter)	DC5V, 3A
Paper width	57.5± 0.5mm
Paper roll diameter	60mm (Max.)
MCBF	5 million lines
Auto cutter type	Guillotine
Auto cutter life	5,000,000 cuts
Auto cutter method	Partial cut
Interface	RS-232/Parallel/USB/RS-485
Paper supply method	Drop-in Easy Loading
Power supply:	DC9~24V±10%, 2A
Dimension (L x W x H)	109x101x68mm
Weight	185g
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C / 10%-90%
Installation port dimension (LxWxH)	103 x 95x 65mm

Shenzhen HCC Technology Co., Ltd.
Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
Post Code:518057 Tel:86-755-86655162 Fax:86-755-8606-9640 Web:www.szhcct.com

Picture



Shenzhen HCC Technology Co., Ltd.

Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
Post Code:518057 Tel:86-755-86655162 Fax:86-755-8606-9640 Web:www.szhcct.com