

		Shenzhen Zecre Technology Co., Ltd Add.: 5th floor, B Building, Debaoli Industrial Park, Bantian, Longgang, Shenzhen Tel.: 0755-28367890 Mob.: +86 13332935176 E-mail: anna.ruan@zecre.com Website: www.zecre.com	
Model		PH770-5S	
Key Features			
	Image Sensor	1/2.7-Inch 5-Megapixel(2592*1944) CMOS	
	Stand-by Time	Approx 8 months	
	Range of IR Flash	120 degree, Range of IR flash 20M	
	Trigger Times	0.2-0.6 sec super fast trigger times	
	HD Quality	32MP 4K high quality images & videos	
	Black Low Glow 940NM IR LED/ 940NM	45 pieces The 'Black No Glow' covert infrared flash LED provides a 65 feet flash range in the dark, which makes it a stealthy unit that does not intrude into the natural habitat.	
Specification			
	Image sensor	1/2.7-Inch 5Megapixel(2592*1944) CMOS Sensor	
	Lens	Focal Length=4mm F/NO=2.0 View Angle=98°	
	Storage Media	SD Card, up to 512GB	
	Mode	Photo	
		Video	
		Photo*Video	
	Photo resolution	32.0 Mega pixels	
		24.0 Mega pixels	
		20.0 Mega pixels	
		16.0 Mega pixels	
		12.0 Mega pixels	
		8.0 Mega pixels	
	Photo Series	5.0 Mega pixels	
		1Photo	
		2 Photo in series	
		3 Photo in series	
	Video resolution	4K: 3840*2160	
		2.7K: 2688*1520	
		1080P: 1920*1080	
		720P: 1280*720	
		720P: 1280*720 (60pfs)	
		D1: 720*480	
		VGA: 640*480	
	File format	JPEG/AVI(H.264)	
	IR Filter	Full Automatic IR Filter	
	TFT LCD Display Screen	48x35.69mm (2.36");480(RGB)*234DOT; 16M color	
	Main PIR sensor angle	40°	
	Side PIR sensor angle	L: 30° R: 30°	
	Dual PIR sensor angle	120°	
	PIR Sensing Distance	65ft/20 meters	
	Number of IR LED	45 IR LEDs	
	Max Night Vision Lighting Distance	65ft/20 meters	
	Trigger Times	0.2-0.6 sec super fast trigger times	
	Low Battery Auto Power Off	support	
	Triggering Interval	5second ~ 60mins (default 60 sec)	
Date Time Imprint	Yes		
Moon Phase Imprint	Yes		
Ambient Temperature Imprint	Yes		
Serial NO. Imprint	Yes		
Exposure	Auto		
Pass Word Set	4 bit, Digits and 26 alphabet set by yourself		
Device Serial No. Set	4 bit, Digits and 26 alphabet set by yourself		
Time Switch	support		
Periodic shot	0Second~24Hours		
Stand-by current	Lower than 0.2mA		
Stand-by Time	Approx 8 months		
Built-in MIC	Yes		
Built-in Speaker	Yes		
Interface	External: TV out (NTSC/PAL,MiniUSB); MiniUSB; SD Card Holder; 6V DC Power Jack		
Fix Method	Bandage, Iron Bracket (1/4 Inch Standard Interface)		
Operation Temperature	-20 ~ 60°C		
Operating humidity	5% ~ 90%		
Power Source	4-8 AA Battery DC :6V-1.5A		
Water proof Standard	IP66		
Language	English/Deutsch/Dansk/Suomi/Svenska/Espanol/ Francais/Italiano/Nederlands/Portugues/Chinese		
Security authentication	CE, FCC, ROHS, WEEE, MSDS		
Packing list			
	Product size	141.8x 108.5 x 72.6mm	
	Color box size	180*110*110mm	
	Net weight	650g	
	Carton size	20pcs/ctn 38.5*32.5*46 cm	
	Accessories	Mini USB Cable, Strap, User Manual, Wall Mount, Screws	