


推荐插头尺寸



规格:

1. 额定值: DC30V 4A
 2. 接触电阻: $\leq 30\text{m}\Omega$
 3. 绝缘电阻: $\geq 100\text{M}\Omega$
 4. 耐电压: 500VAC
 5. 插拔力: 3N $\sim$ 30N
 6. 使用寿命: 10000次
 7. 使用温度: $-20^{\circ}\text{C}\sim+80^{\circ}\text{C}$
- 符合协会要求

P.C.B 设计参考尺寸

8					TOLERANCE UNLESS SPECIFIED									
7														
6	PANEL	SUS	1		WITHIN 1.5: ±0.1mm OVER 1.5: ±0.25mm ANGLES: ±2°									
5	COVER	BRONZE	1	COPPER Tin			ISSUE	DATE		DESCRIPTIONS	APPD.			
4	HOUSING	PA9T	1	BLACK	TITLE:DC JACK		UNIT:mm		DRWG. NO.:					
3	TERMINAL	BRASS	1	COPPER Tin	MODEL NO: DC-044A 短柱		SCALE:4:1		DWN	YINONG				
2	SPRING	BRONZE	1	COPPER Tin					CHK'D	ZHENGZHIHUI				
1	PIN	BRASS	1	COPPER Tin	DONGGUAN CITY JINBELLI ELECTRICAL TECHNOLOGY CO.,LTD							APPD.	LILUSUN	
NO.	DESCRIPTION	MATERIAL	QTY	PLATING										