

Winstars®	Winstars Product Specifications			Version	A0						
				Page	1/1						
	Model	WS-UH3048C			Date	2015.04.20					
	Name	4 Port USB 3.1 HUB			Writer		chen				
Picture tupia 图片				Features: 特点							
				• supportr UP-stream Port Type C • Support usb3.1 Gen1 • 4 down-stream ports support transfer rates up to 5Gbps • Support hot swapping, Plug and Play to reach user friendly • Led indicators display power ON/OFF • Slef-powered properties • Build in surge protector in each port to the computer safety • Supports Microsoft Windows XP/Vista/7/8 or later & MAC OS X /Linux • Backward compatible with USB 3.0/ USB 2.0							
Title 标题											
4 Port USB3.1 Type C HUB											
Description 介绍				Package content 标配		SYSTEM REQUIREMENT: 系统配置					
4-Port high performance USB 3.0 SuperSpeed Hub and Sleek compact design Self-powered properties for Ultrabook / Laptop / Tablet partner Overall arrangement make to become user friendly				USB 3.0 4-Port HUB X1		USB 2.0/3.0 Type C Port					
It can be used on USB 3.0 HDD, High-resolution camera, Video surveillance cameras, digital video cameras and variety of audio and other peripheral devices						Note: Some USB 3.0 host card require installation newest driver for the USB divece to reach optimal USB 3.0 compatible performance.(recommeded).					
Specification 规格											
Hardware 硬件				Functions 功能							
Ports	4 x USB 3.0, 1 x DC			Working Standards	USB 3.0 5Gbps Led indicators						
Button	NIL										
LED	blue colour led										
Chipset	GL3520										
Flash	PM25LD512			Operating System Support	Windows XP/Vista/7/8 Mac OS 10.2 or above Linux						
SDRAM	NIL										
Power Supply	Slef-powered										
Power Plug	NIL			Max Pixels	NIL						
Power Consumption	0.5W			Max charing current(A)	NIL						
Rated Voltage/ requency /current		NIL									
Dimensions 尺寸				Certification 证书							
Unit Dimensions	112X35x16 MM (L x W x H)			CE-EMC			NO suitable				
Weight	50G			CE-RTTE							
Housing Material	Aluminum alloy			CE-LVD							
Shell color	Aluminum alloy silver			FCC DOC							
Package Dimensions	220*148*68 (L x W x H)			FCC ID							
Environmental 环境				ROHS							
Operating Temperature		0°C~40°C		Reach							
Storage Temperature		-10~70°C		3C							
Relative Humidity(Operational)		10%~90%,noncondensing		Others 其他							
Relative Humidity(Storage)		10%~90%,noncondensing		Method	See Manual						
Drop test (1 Meters)		5 st		Performance	See Test Report						
Cycle work (hours)		24H		Reliability	See Test Report						