

	SoC	ASR1803S CAT4 / ASR5803W	
	Dimension	98*66*15mm	
	Bands	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)	
	Form factor	MIFI	
	Battery	Li-ion Battery 2100mAh Working time: 5-6 hrs, Standby time: around 300 hrs (Depend on network)	
	Wi-Fi	802.11 b/g/n, WIFI speed up to 72Mbps, max 10 users connection	
	Memory	256Mb RAM	
	Data Rates	LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL	
	Hardware	USB	USB2.0, Type C
		SIM	2FF (eSIM / VSIM optional)
		LED	Battery/WIFI/Signal
		Antenna	Build-in FPC type
		Power Voltage	USB DC 5V
		Button	Reset(Pinhole), Power
	Software	Update	FOTA & Local update
		Support OS	Compatible with Windows / MACOS / Linux / Android IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics,
		Others	WIFI Security
	Operation Temperature	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80% Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%	

Model: L816A



LTE Cat4 ASR1803S/L Cost effective Solution
eSIM/VSIM support optional