

MICR & MSR Check Reader HCC1250X-M

General

HCC1250 MICR check reader can read check or other bill with magnetic ink characters automatically, and can read magnetic card with manual swipe. It is widely used in all kinds of financial transaction and information checking area, such as banking, retailing, market, hotel, etc.

Feature

- Compact size, horseshoe
- Secure/reliable reading, good pass read rate in the first time, single sheet at one time
- Motorized paper transport for quick, easy check handling
- Interface: RS232, PS/2, USB (HID or Virtual COM)
- Integrated Mag-strip card reader, dual or triple tracks
- Applicable to many operating systems: UNIX, WINDOWS, NT and OS/2, etc

Specification

MICR standard	ISO1004 standard E13B, CMC7
MSR standard	ISO/IBM format, dual tracks or triple tracks
Reading indication	Green/red status LED for right/error reading
Mufty interface	RS232, IBM PC/AT/XT, USB (HID or Virtual COM) 2400/4800/9600/19200 bps at option under RS232 interface
Feeding speed	250mm/sec (± 30 mm/sec)
Reading speed	1.2sec/sheet (with 157mm sheet length)
Power supply	DC+12V
Head lifetime	500,000cycles
Recognition accurate rate	98% for E13B&CMC7 &MSR
Power	DC12V $\pm 10\%$,1000mA DC5V $\pm 10\%$,1000mA USB BUS power 5V, 400mA

Model Description

1250x1-x2

Type	X1	Interface	X2	Magnetic Module
1250 (MICR)	R	RS232 Series port	0	No
	K	PS/2	M	1&2&3 tracks
	UH	USB HID		
	UV	Virtual COM		



Picture

