

HENEX

2D WIRELESS BARCODE SCANNER HC-3208SRC



1.3MP image frame rate up to 120fps Max

3-in -1 transmission: Cradle +BT+Type-B Cable

Can read all 1D/2D/Dotcode barcode on the screen and paper

Support double firmware upgrade online: wireless and decoder.

Support for offline storage mode,can memory 380,000 characters (EAN-13 code)

APPLICATION

logistics, express, Warehouse inventory,Tobacco,
Health care or some industrial business



1.3M pixel



1D/2D



one key pairing ,
one key upload data



Quick
reading



Plug and
play



Three color
indicator



Automatic
scan



Anti seismic
anti falling

HC-3280SRC TECHNICAL SPECIFICATION

CPU 950 MHZ dual-core + 0.2T NPU	Image Sensor Global shutter	Image(Pixels) 1080×1280 CMOS	light source Aiming: Red light LED; illumination:White light LED	Scan Mode Handhand (Manual) / Handfree (Automatic)
Frame Rate 120fps/s Max	Scan accuracy ≥ 4mil	Print Contrast ≥ 20%	Visual Indicator Red, blue and green LED lights Buzzer and motor vibration	Transmission Range 2.4G: 100meters, Bluetooth HID: 40meters (On open air)
Scan Angle Tilt: 360°, Pitch: ±55°, Roll: ±70°	Field of view 40° horizontal, 31° vertical	Work frequency 2.400GHz-2.480GHz ISM	Dimension L x W x H 173*66*94 (mm)	Weight 202g
Case Material ABS+PC, TPU	Memory Capacity 380000 byte	Power parameter Input Voltage: 5VDC±5% Working current: 400mA	Scan distance 50-450mm @ EAN 13mil PCS=100%; 70-250mm @ Code39 5mil PCS=100% 30-300mm @ DM 13mil PCS=100%	
Battery Parameters Battery Capacity: 2000mAh Charge Mode: Wire charging / seat charging Charge time: 5 h Working time: 12h (continuous scanning)		Safety regulations CE (EN 55032:2015; EN 55035:2017), ROHS, BIS, EN62368-1:2014+A11:2017 FCC PART 15 CLASS B	Environmental parameters Operating Temperature: -10°C~+ 50°C Working Humidity: 5% to 95% relative humidity, non-condensing Storage Temperature: -20°C~+60°C Electrostatic protection: ±8 kV (Direct discharge) Ambient brightness: 0~100,000Lux Drop Resistance : 1.6M IP: IP42	

Decoding Capability

1D: Codabar, Code11, Code128, ISBT128, Code32, Code39, TLC39, Code93/93i, BC412, UK Plessey, Anker Plessey, EAN-13, EAN-8, GS1, MSI Plessey, Telepen, Pharma, PatchCode, UPC-A, UPC-E, China Post, Interleaved 2 of 5, Matrix 2 of 5, NEC 2 of 5, Standard 2 of 5, IATA 2 of 5, Industrial 2 of 5, etc.

2D: Data Matrix, MaxiCode, QR, Micro QR, rMQR, Aztec Code, Han Xin, Dot Code, Grid Matrix, Codablock A, Codablock F, PDF417, Micro PDF417, OCR-A/B

Postal: China Post, Korea Post, Australia Postal, Royal INFOMAIL, Japan Postal, KIX, PLANETCODE, POSTNET, Britain Postal, UPU, USPS 4STATE

Cradle Parameters

Dimension H x W x L 122*75*94 (mm)	Weight 132g (No with cable)	key-press one key pairing , one key upload data	Paired Mode one to one, or one to more (Optional)	Cable Standard 1.5M straight
Power parameter Input Voltage: 5VDC±5% Working current: 400mA				

Optional configuration

Cradle	USB Dongle
--------	------------