











Dimensions

Unit:mm

No.	Photo	Style																																																
1		 Rating: 125V AC 0.3A Timing: Shorting or Non-Shorting L=10~45mm D=6mm CHANGEOVER ANGLE=30° <table><tr><th>ORDER NO.</th><th>SW. FUNCTION</th><th>ORDER NO.</th><th>SW. FUNCTION</th></tr><tr><td>H25-1-1-2</td><td>SP 2 POS.</td><td>H25-1-2-2</td><td>DP 2 POS.</td></tr><tr><td>H25-1-1-3</td><td>SP 3 POS.</td><td>H25-1-2-3</td><td>DP 3 POS.</td></tr><tr><td>H25-1-1-4</td><td>SP 4 POS.</td><td>H25-1-2-4</td><td>DP 4 POS.</td></tr><tr><td>H25-1-1-5</td><td>SP 5 POS.</td><td>H25-1-2-5</td><td>DP 5 POS.</td></tr><tr><td>H25-1-1-6</td><td>SP 6 POS.</td><td>H25-1-2-6</td><td>DP 6 POS.</td></tr><tr><td>H25-1-1-7</td><td>SP 7 POS.</td><td>H25-1-3-2</td><td>3P 2 POS.</td></tr><tr><td>H25-1-1-8</td><td>SP 8 POS.</td><td>H25-1-3-3</td><td>3P 3 POS.</td></tr><tr><td>H25-1-1-9</td><td>SP 9 POS.</td><td>H25-1-3-4</td><td>3P 4 POS.</td></tr><tr><td>H25-1-1-10</td><td>SP 10 POS.</td><td>H25-1-4-2</td><td>4P 2 POS.</td></tr><tr><td>H25-1-1-11</td><td>SP 11 POS.</td><td>H25-1-4-3</td><td>4P 3 POS.</td></tr><tr><td>H25-1-1-12</td><td>SP 12 POS.</td><td>H25-1-6-2</td><td>6P 2 POS.</td></tr></table>	ORDER NO.	SW. FUNCTION	ORDER NO.	SW. FUNCTION	H25-1-1-2	SP 2 POS.	H25-1-2-2	DP 2 POS.	H25-1-1-3	SP 3 POS.	H25-1-2-3	DP 3 POS.	H25-1-1-4	SP 4 POS.	H25-1-2-4	DP 4 POS.	H25-1-1-5	SP 5 POS.	H25-1-2-5	DP 5 POS.	H25-1-1-6	SP 6 POS.	H25-1-2-6	DP 6 POS.	H25-1-1-7	SP 7 POS.	H25-1-3-2	3P 2 POS.	H25-1-1-8	SP 8 POS.	H25-1-3-3	3P 3 POS.	H25-1-1-9	SP 9 POS.	H25-1-3-4	3P 4 POS.	H25-1-1-10	SP 10 POS.	H25-1-4-2	4P 2 POS.	H25-1-1-11	SP 11 POS.	H25-1-4-3	4P 3 POS.	H25-1-1-12	SP 12 POS.	H25-1-6-2	6P 2 POS.
ORDER NO.	SW. FUNCTION	ORDER NO.	SW. FUNCTION																																															
H25-1-1-2	SP 2 POS.	H25-1-2-2	DP 2 POS.																																															
H25-1-1-3	SP 3 POS.	H25-1-2-3	DP 3 POS.																																															
H25-1-1-4	SP 4 POS.	H25-1-2-4	DP 4 POS.																																															
H25-1-1-5	SP 5 POS.	H25-1-2-5	DP 5 POS.																																															
H25-1-1-6	SP 6 POS.	H25-1-2-6	DP 6 POS.																																															
H25-1-1-7	SP 7 POS.	H25-1-3-2	3P 2 POS.																																															
H25-1-1-8	SP 8 POS.	H25-1-3-3	3P 3 POS.																																															
H25-1-1-9	SP 9 POS.	H25-1-3-4	3P 4 POS.																																															
H25-1-1-10	SP 10 POS.	H25-1-4-2	4P 2 POS.																																															
H25-1-1-11	SP 11 POS.	H25-1-4-3	4P 3 POS.																																															
H25-1-1-12	SP 12 POS.	H25-1-6-2	6P 2 POS.																																															
2		 Rating: 125V AC 0.3A Timing: Shorting or Non-Shorting L=10~45mm D=6mm CHANGEOVER ANGLE=30° H25- P SW. FUNCTION similar to H25- H																																																
3		 Rating: 125V AC 0.3A Timing: Shorting or Non-Shorting L=10~40mm D=6mm CHANGEOVER ANGLE=30° HP25 SW. FUNCTION similar to H25																																																