

	1	2	3	4	5	6	7	8	9																																																																				
G	RoHS																																																																												
F	芯 数/NO. of contacts 面板开孔/RECOMMENDED PANEL CUT-OUT																																																																												
E	<table> <tr> <th>系 列/Series</th><th>303A</th><th>304A</th><th>305A</th><th>306A</th><th>307B</th><th>308A</th><th>312A</th><th>314B</th><th>319A</th></tr> <tr> <td>孔位排列/Pin Number</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>适配线缆/Conductor size</td><td>0.75mm²</td><td>0.75mm²</td><td>0.75mm²</td><td>0.75mm²</td><td>0.75mm²</td><td>0.75mm²</td><td>0.25mm²</td><td>0.25mm²</td><td>0.25mm²</td></tr> <tr> <td>导体直径/Pin size</td><td>1.5mm</td><td>1.5mm</td><td>1.5mm</td><td>1.5mm</td><td>1.5mm</td><td>1.5mm</td><td>1.0mm</td><td>1.0mm</td><td>1.0mm</td></tr> <tr> <td>额定电流/Rated current</td><td>7A</td><td>6A</td><td>6A</td><td>5A</td><td>5A</td><td>5A</td><td>3A</td><td>3A</td><td>3A</td></tr> <tr> <td>额定电压/Rated voltage</td><td>250V</td><td>250V</td><td>250V</td><td>250V</td><td>125V</td><td>60V</td><td>60V</td><td>60V</td><td>60V</td></tr> </table>									系 列/Series	303A	304A	305A	306A	307B	308A	312A	314B	319A	孔位排列/Pin Number										适配线缆/Conductor size	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.25mm ²	0.25mm ²	0.25mm ²	导体直径/Pin size	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.0mm	1.0mm	1.0mm	额定电流/Rated current	7A	6A	6A	5A	5A	5A	3A	3A	3A	额定电压/Rated voltage	250V	250V	250V	250V	125V	60V	60V	60V	60V								
系 列/Series	303A	304A	305A	306A	307B	308A	312A	314B	319A																																																																				
孔位排列/Pin Number																																																																													
适配线缆/Conductor size	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.25mm ²	0.25mm ²	0.25mm ²																																																																				
导体直径/Pin size	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.0mm	1.0mm	1.0mm																																																																				
额定电流/Rated current	7A	6A	6A	5A	5A	5A	3A	3A	3A																																																																				
额定电压/Rated voltage	250V	250V	250V	250V	125V	60V	60V	60V	60V																																																																				
D	技术特性/Technical Characteristics 1. 寿命/Durability: >500 mate/unmate cycles 2. Pin接触电阻/ Pin Contact Resistance: ≤10 mΩ 3. 绝缘电阻/Insulation Resistance: ≥ 100 MΩ 4. 温度等级/Rated Temperature: -25° C,+80° C 5. 盐雾/Corrosion Resistance: Salt spray test,>48h 6. 防水等级/Waterproof: IP40																																																																												
C	<table> <tr> <td>4</td><td>螺母/Nut: 黄铜镀镍/Brass,Nickel plated</td></tr> <tr> <td>3</td><td>外壳/Outer Shell: 锌合金镀镍/ Zinc Alloy,Nickel plated</td></tr> <tr> <td>2</td><td>公针芯/PIN: 黄铜镀金/Brass,G/F</td></tr> <tr> <td>1</td><td>绝缘体/Insulator: PA BLACK</td></tr> <tr> <td>序号ITEM</td><td>名称 & 规格/Name & Description</td></tr> </table>									4	螺母/Nut: 黄铜镀镍/Brass,Nickel plated	3	外壳/Outer Shell: 锌合金镀镍/ Zinc Alloy,Nickel plated	2	公针芯/PIN: 黄铜镀金/Brass,G/F	1	绝缘体/Insulator: PA BLACK	序号ITEM	名称 & 规格/Name & Description																																																										
4	螺母/Nut: 黄铜镀镍/Brass,Nickel plated																																																																												
3	外壳/Outer Shell: 锌合金镀镍/ Zinc Alloy,Nickel plated																																																																												
2	公针芯/PIN: 黄铜镀金/Brass,G/F																																																																												
1	绝缘体/Insulator: PA BLACK																																																																												
序号ITEM	名称 & 规格/Name & Description																																																																												
B	<table> <tr> <th></th><th></th><th></th><th></th><th colspan="2">OPERATION</th><th rowspan="2">DRAW</th><th rowspan="2">Lu jin ying</th><th></th><th>SCALE</th><th>FIT</th><th colspan="2" rowspan="4"> HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD </th></tr> <tr> <th></th><th></th><th></th><th></th><th>X.X</th><th>±0.30</th><th></th><th>UNIT</th><th>mm</th></tr> <tr> <th></th><th></th><th></th><th></th><th>X.XX</th><th>±0.20</th><th rowspan="2">CHECK</th><th rowspan="2"></th><th rowspan="2"></th><th>SIZE</th><th>A4</th></tr> <tr> <th></th><th></th><th></th><th></th><th>X.XXX</th><th>±0.10</th><th>SHEET</th><th>1/1</th></tr> <tr> <th>A0</th><th>2022.12.01</th><th colspan="2">NEW DRAWING</th><th>Angle</th><th>±3°</th><th rowspan="2">APPROVE</th><th rowspan="2"></th><th rowspan="2"></th><th>PROJ.</th><th></th><th>PART NO.</th><th>HC-M16M0XXXAMABG1</th></tr> <tr> <th>REV</th><th>DATE</th><th colspan="2">MODIFICATION DESCRIPTION</th><th>DIM</th><th>TOL</th><th></th><th></th><th>TITLE:</th><th>Fixed socket</th></tr> </table>																	OPERATION		DRAW	Lu jin ying		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD						X.X	±0.30		UNIT	mm					X.XX	±0.20	CHECK			SIZE	A4					X.XXX	±0.10	SHEET	1/1	A0	2022.12.01	NEW DRAWING		Angle	±3°	APPROVE			PROJ.		PART NO.	HC-M16M0XXXAMABG1	REV	DATE	MODIFICATION DESCRIPTION		DIM	TOL			TITLE:	Fixed socket
				OPERATION		DRAW	Lu jin ying		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD																																																																		
				X.X	±0.30				UNIT	mm																																																																			
				X.XX	±0.20	CHECK			SIZE	A4																																																																			
				X.XXX	±0.10				SHEET	1/1																																																																			
A0	2022.12.01	NEW DRAWING		Angle	±3°	APPROVE			PROJ.		PART NO.	HC-M16M0XXXAMABG1																																																																	
REV	DATE	MODIFICATION DESCRIPTION		DIM	TOL						TITLE:	Fixed socket																																																																	
A	1	2	3	4	5	6	7	8	9																																																																				