

Specification	
Size Mini-ITX, 170mm*170mm	Audio interface Realtek ALC662 HD Support Line-In,Line-out,MIC-in port, Supports 5W amplifier
CPU Support Intel LGA1150(Haswell) Processor	I/O Expansion 6*USB2.0 (4*USB2.0 Extensibl) , 2*USB3.0. 6*RS232 COM , 1*RS485 , Support COM port 5V/12V for power
Chipset Intel H81	Watchdog Support CPU temperature detection, fan speed, system temperature.
Memory 1* SO-DDR3 1333/1600M Memory, Up Max to 8GB.	Expansion bus 1* MINIPCIe expansion slot , Support WIFI/3G,1*MSATA port , support MSATA,1*PCIe4X, Support independent graphic cards.
Display port Intel CPU built-in display core, support VGA, dual HDMI interface, HDMI pin, LVDS. Built-in double channel 24bit LVDS pin, support dual screen display.	Operation Environment Power: Recommended DC12V10A/19V7A working tem.: 0~60 degree centigrade Working Humidity: 5%~95%, non-condensing
Storage 2*SATA2.0 , 1*MSATA Port , Max transmission speed 3.0 Gbps.	BIOS AMI BIOS , support write protection.Power on, time to boot, remote switch machine intelligent identification
Network interface 1*Realtec8111F 1000M LAN port , Support network wake-up. Optional support for dual networks	Operating system WINDOWS 7 -32 bit, 64 bit, Windows 8, Linux.