

DAEWOO

CMC-725BF

Full Flat

17" Color Monitor



SPECIFICATIONS

CRT	Size	17" Flat
	Viewable size	16"
	Dot Pitch	0.25mm
	Phosphor	RGB medium-short persistence
	Surface treatment	Anti-Glare/Anti-Static coating
Scanning Frequency	Horizontal	30 ~ 70KHz
	Vertical	50 ~ 160Hz
Bandwidth		110MHz
Resolution	Maximum	1280 x 1024 @ 60Hz
	Recommended	1024 x 768 @ 85Hz
Display Area	Normal	310mm(H) x 235mm(V)
	Maximum	330mm(H) x 250mm(V)
Input Signal	Video	RGB Analog (C.V/1.0Vp-p, 75ohms)
	Sync	H/V Separate (TTL), Composite
Input Signal Connector		15pin D-Sub
Plug & Play		DDC 1/2B/C1
USB (optional)	Stand Based-on Hub	1 upstream, 4 downstream
User Control Button		Power on/off, Menu, Down, Up, Left, Right
On Screen Display Control	Hot Key Control	Contact, Brightness
	Size	H-Size, V-Size
	Center	H-Center, V-Center
	Geometry	Pin-cushion, Trapezoid, Pie-Balance, Parallelogram, T.Pin-Corner, S.P. corner, Rotation(Optional)
	Color	Color Temperature (9300°K/6500°K / User), R-Gain, G-Gain, E-Gain
	Utility Language	DeGauss, Status, H/V-Moire, Recall, 5 Languages (Eng, Dew, Jap, Fre, Ital)
Power Voltage		AC 100 ~ 240v @ 60/50Hz, Universal Power
Power Saving	On	85 WATT
	Suspend/Stand-by	15 WATT
	OFF	5 WATT
Audio (optional)	Speakers & Controls	1.7W two-way, Power on/off, Volume
Dimension (with Stand)	W x H x D	410mm x 407mm x 419mm
Weight	Net	10.0kg
	Gross	18.6kg
Regulation	Low Radiation	MPR II, TCO99 (optional)
	Safety & Ergonomics	UL, CSA, DHHS, GS, EMKO, PCBC
	EMC (EMI/EMS)	FCC 2, CE, VCCI (Optional)
Power Management		EPA Energy Star, VESA DPMS Compliant
Environmental Conditions	Operating	Temperature : 10 to 40°C Humidity : 8 to 80% (non-condensing)
	Storage	Temperature : -10 to 45°C Humidity : 5 to 90% (non-condensing)

