




WINGED WIRE CONNECTORS

Features

- UL 486C Listed and CSA 22.2 No. 188 Certified.
- Tough thermoplastic, UL 94V-2 flame-retardant shell.
- Rated at 600 V Max. for building wiring and 1000 V Max. in lighting fixtures/luminaries and signs.
- Five color-coded to industry standards.
- Available in socket tools for easy installation of connectors (See page 9).
- Can be supplied under private label packaging.



Dimensions



| Model | A | | B | | C | | D | | E | |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | mm | in. | mm | in. | mm | in. | mm | in. | mm | in. |
| P11 | 6.40 | 0.252 | 9.80 | 0.386 | 28.20 | 0.717 | 9.00 | 0.354 | 25.80 | 1.016 |
| P12 | 7.20 | 0.283 | 11.60 | 0.457 | 18.30 | 0.720 | 9.20 | 0.362 | 29.00 | 1.142 |
| P13 | 9.00 | 0.354 | 13.00 | 0.512 | 23.00 | 0.906 | 9.60 | 0.378 | 31.80 | 1.252 |
| P15 | 10.00 | 0.394 | 14.90 | 0.587 | 25.50 | 1.004 | 10.00 | 0.394 | 33.30 | 1.311 |
| P17 | 12.00 | 0.472 | 17.80 | 0.701 | 32.00 | 1.260 | 13.00 | 0.512 | 40.00 | 1.575 |

Ratings

| Model | Color | Elec. Rating & Wire Range | Approval | | | Packing | Cat. No. |
|------------|--------|--|----------|--|--|---|--------------|
| P11 | Yellow | 600 V Max. Temp. 105°C (221°F) No. 18 - No. 10 AWG Max. 3 #12 Sol Min. 2 #18 | | | | Box of 100 | P1100 |
| | | | | | | Ctn of 5,000 (10 plastic bags, 500 ea) | P1101 |
| | | | | | | Bag of 25 (Bag packed with header) | P1102 |
| P12 | Tan | 600 V Max. Temp. 105°C (221°F) No. 22 - No. 8 AWG Max. 4 #12 Min. 3 #22 Sol | | | | Box of 100 | P1200 |
| | | | | | | Ctn of 5,000 (10 plastic bags, 500 ea) | P1201 |
| | | | | | | Bag of 25 (Bag packed with header) | P1202 |
| P13 | Red | 600 V Max. Temp. 105°C (221°F) No. 18 - No. 8 AWG Max. 5 #12 Sol Min. 3 #16 | | | | Box of 100 | P1300 |
| | | | | | | Ctn of 5,000 (10 plastic bags, 500 ea) | P1301 |
| | | | | | | Bag of 25 (Bag packed with header) | P1302 |
| P15 | Grey | 600 V Max. Temp. 105°C (221°F) No. 18 - No. 8 AWG Max. 3 #10 Min. 3 #14 w/1 #18 | | | | Box of 50 | P1500 |
| | | | | | | Ctn of 2,500 (10 plastic bags, 250 ea) | P1501 |
| | | | | | | Bag of 6 (Bag packed with header) | P1502 |
| P17 | Blue | 600 V Max. Temp. 105°C (221°F) No. 14 - No. 6 AWG Max. 3 #8 w/1 #12 Min. 2 #10 w/1 #12 | | | | Box of 50 | P1700 |
| | | | | | | Ctn of 1,500 (15 plastic bags, 500 ea) | P1701 |
| | | | | | | Bag of 6 (Bag packed with header) | P1702 |