

										
Model	D410	D410S	M411	M412	M710	N210	N210S	U211	X410	X412
Screen Size	23.8"	23.8"	23.8"	23.8"	27"	21.5"	21.5"	21.5"	23.8"	23.8"
Resolution	1920*1080	1920*1080	1920*1080	2560*1440	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Display Type	VA	VA	VA	IPS	TN	IPS	IPS	ADS	IPS	IPS
Brightness	250cd/m²	250cd/m²	250cd/m²	250cd/m²	250cd/m²	250cd/m²	250cd/m²	250cd/m²	250cd/m2	250cd/m²
Response Time	2ms	2ms	2ms	2ms	2ms	2ms	2ms	2ms	2ms	2ms
Inputs	USB2.0*2, USB3.0*4, HDMI*1, VGA*1, Audio-in, RJ45	USB2.0*5, USB3.0*1, HDMI*1, VGA*1, Audio-in, RJ45	USB2.0*1, USB3.0*4, HDMI*1, VGA*1, Audio-in, RJ45	USB2.0*4, SD Reader, USB3.0*2, HDMI*2, Audio-in, RJ45	USB2.0*4, SD Reader, USB3.0*2, HDMI*2, Audio-in, RJ45	USB2.0*1, USB3.0*4, HDMI*1, VGA*1, Audio-in, RJ45	USB2.0*4, USB3.0*1, HDMI*1, VGA*1, RJ45	USB2.0*5, SD Reader, USB3.0*1, HDMI*1, Audio-in, RJ45, USB-C*1	USB2.0*2, USB3.0*4, HDMI*1, VGA*1, Audio-in, RJ45	USB2.0*4, SD Reader, USB3.0*2, HDMI*2, Audio-in, RJ45
Mainboard	Intel H110	Intel Baytrail Chipset	Intel H110	Intel H110	Intel H110	Intel H110	Intel H110	Intel H110	Intel H110	Intel H110
Video Card	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Radiator	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Independent Copper Tube Heat Dissipation Module	Integrated	Integrated
Speaker	High Quality	High Quality	High Quality	High Quality	High Quality	High Quality	High Quality	High Quality	High Quality	High Quality
WIFI	High Gain	High Gain	High Gain	High Gain	High Gain	High Gain	High Gain	High Gain	High Gain	High Gain
CPU	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)	NA (Supports Intel 6th/7th Generation 1151)
Memory	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)	NA (Supports DDR4)
Hard-Disk	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports M.2 & SSD 2.5")	NA (Supports SSD 2.5")	NA (Supports SSD 2.5")
Power Range	110V~220V 90W	110V~220V 90W	110V~220V 180W	110V~220V 180W	110V~220V 180W	110V~220V 90W	110V~220V 48W	110V~220V 90W	110V~220V 90W	110V~220V 180W
VESA Mounting	NA	NA	NA	NA	NA	100*100mm	100*100mm	NA	NA	NA
Dimensions	538*395*54mm	538*395*54mm	539*390*65mm	538*390*54mm	610*435*65mm	508*303*62mm	508*303*62mm	489*389*46mm	538*395*54mm	538*395*54mm
Color	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Black/White	White