

标配组件 Standard components 凹轮、斜面轮、圆弧轮可选 Concave wheel, inclined wheel, and circular wheel are optional

配件名称 Accessory Name	图示 Diagram	使用数量 Quantity used	配件名称 Accessory Name	图示 Diagram	使用数量 Quantity used
阻尼滑轮 Buffer pulley		2	限位件 Limiting element		4
			方形定位件 Square positioning piece		4
滑轮 pulley		4	皮带 belt		1
齐平联动滑轮挂盒 Guide wheel hanging box		2	伸缩杆 Telescopic rod		1
齐平联动皮带夹挂盒 Belt clamp box		2	M5*6内六角盘头螺丝 M5*6 hex socket pan		2
115铝挂盒 115 aluminum hanging box		2	M4*12内六角固定螺丝 M4*12 hex socket set screw		16
弹跳轮 Bouncing wheel		2	2.0/2.5/3.0/4.0内六角扳手 2.0/2.5/3.0/4.0 hex wrench		1
防撞轮 Anti swing wheel		2	上轨道 Upper orbit		3

技术参数 Technical Parameter

主要材质: 深沟球轴承、钢材、锌(铝)合金、尼龙  
表面处理: 电泳黑(也可按需求定制)  
适用范围: 极窄铝框门  
单门承重: 80KG  
包装规格: 盒装、12付/箱

Main materials: deep groove ball bearings, steel, zinc (aluminum) alloy, nylon  
Surface treatment: Electrophoretic black (can also be customized according to needs)  
Scope of application: Extremely narrow aluminum frame doors  
Single door bearing capacity: 80KG  
Packaging specifications: boxed, 12 pairs/box

安装尺寸参数计算公式:  
Calculation formula for installation size parameters:

门洞高=H / 门高=h / 门洞宽=W / 门宽=w / 门厚=T  
门高h≤H-80  
门宽w=(W+2×重叠尺寸C)÷3  
门宽: w≥610MM

Door height=H / Door height=h / Door width=W / Door width=w / Door thickness=T  
Door height h ≤ H-80  
Door width w=(W+2 x overlapping dimension C) ÷ 3  
Door width: w ≥ 610MM

