

8300PLUS FAST CUT RUBBING COMPOUND



Product Description



#8300Plus Fast Cut Rubbing Compound offers rapid removal of minor surface defects and swirl marks from all modern paint systems. #8300Plus Compound is a one-step system that provides a fast cutting action and a high gloss finish. It combines all the reliability and other advantages of 300Plus Paste Compound with a reduced clean up time when compounding by machine. It provides the user with improved versatility, quality and speed to final finish verses competitive products.

Key Benefits, special features

Silicone Free:	100% body shop safe
Permanent Finish:	Contains no fillers so scratch marks will not reappear.
Cut/Polish two in one:	Removes P1200 marks and final with excellent gloss. Can be used with 7000B Finishing Compound for an enhanced gloss finish on dark colors.

General Information

Product Group:	Cut and Polish, two in one
Cut/Gloss:	9/8
Lifetime:	3 Years
Storage:	15-25 °C, avoid frost and direct sunlight
Processing(rotary):	800-1200rpm/dry 1500-2500rpm/wet
Processing(orbital):	Depends on manufacturer

Product Information

683PL:	1 liter
683PG01:	1 Gallon
683PL20:	20 liter
683PL200:	200 liter

Consumer Information

- Rapid cutting action
- Permanent gloss finish - No reworks. Scratches are permanently removed to leave an ultimate gloss finish.
- Superior emulsion system - Increased lubrication allows compound to work for longer without drying out.
- Dry use compound - Water is not necessities. Less throw off and significantly improved clean up times.

Technical Information

Colour: White
Density: 1.4 kg/l
Viscosity: Highly Viscous
pH: 9-10
Paint Type Compliance: MS & HS

Polishing System



Use with



Buff Form
Cutting Pad

Complementary Products

Ultra Seal 908
Waterless Wash 201
Cutting Pad W7007 and Polishing Pad W8007
Soft Foam Applicator Pad
Microfiber Towel

Recommended Usage

1. Clean surface thoroughly prior to polishing.
2. Shake the bottle prior to use and apply a small quantity of the product onto the polishing pad (a pea-sized drop is sufficient for an area measuring approx. 40 x 40 cm).
3. Use the Cut Foam Pad W7007 in the event of heavy signs of use. After the sanding marks removed, use the Polish Foam Pad W87007 to remove swirls and holograms.
4. Use either a rotary or an orbital polishing machine and use the cross-coating method. Apply light pressure at the start of the polishing process. Take away the pressure in the final cycles and increase the speed of the polishing machine.
5. If working on very dry coatings, soak the pad, and spin off excess water, to prevent dust formation.
6. At first, the polish will seem a little milky and should be worked in until only a slightly transparent/oily film is visible.
7. Once you have finished polishing, remove any residue with our Microfiber Towel, without applying any pressure.
8. Any signs of sanding and use have now been removed. For an exceptionally glossy finish and protection, apply 908 Ultra Seal.

Important Notice

The above information above represent our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application.

Contacts

Tel: +86-(0)536-2136793
Fax: +86-(0)536-3221079
Mobile: +86- 13815430177 (same wechat id)
Email: kin.you@86leada.com
<https://www.86leada.com/>