

Specifications		Best Accuracy			
Model	Range	9560	9560H	9561	9561H
DC Voltage	60mV/600mV/6V/60V/600V/1000V	±(0.5%+5)		±(0.5%+5)	
	60mV/600mV/6V/60V/600V/1500V		±(0.5%+5)		±(0.5%+5)
AC Voltage	60mV/600mV/6V/60V/600V/1000V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
VFD	50.0V to 700V	±(4.0%+3)		±(4.0%+3)	
	50.0V to 600V		±(4.0%+3)		±(4.0%+3)
DC Current	600μA/6000μA/60mA/600mA/6A/10A	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)
AC Current	600μA/6000μA/60mA/600mA/6A/10A	±(1.5%+3)	±(1.5%+3)	±(1.5%+3)	±(1.5%+3)
Resistance	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ	±(0.8%+2)	±(0.8%+2)	±(0.8%+2)	±(0.8%+2)
Capacitance	99.99nF/999.9nF/9.999μF/99.99μF/ 999.9μF/9.999mF/99.99mF	±(4.0%+5)	±(4.0%+5)	±(4.0%+5)	±(4.0%+5)
Frequency	9.999Hz-9.999MHz	±(0.1%+4)	±(0.1%+4)	±(0.1%+4)	±(0.1%+4)
Temperature	-40°C~1000°C			±(3.0%+3)	±(3.0%+3)
	-40°F~1832°F			±(3.0%+5)	±(3.0%+5)