



SX-203 Single Arm Surgical Pendant



一、 Technical Specifications

- 1、 **Working Power:** AC220V、 50Hz; The pendant overall color is soft and consistent, the gap at the joint should be sealed, gas and electricity are a separating design.
- 2、 **Wishbone motion range(Semidiameter):** 800mm (The range also can be customized by users)
- 3、 Terminal boxes hanging column structure and the length \geq 1000MM, rotating angle: 0 \sim 340 $^{\circ}$, rotating limit device can keep the pendant stable and no drifting.
- 4、 Net load capacity \geq 70KG;
- 5、 Instrument platforms: **two layers**, the tray is primary pressing model, surface treatment is anti-corrosion and anti-rust, single tray load capacity \geq 50kgs, 550mm*400mm*30mm (adjustable height) with 10mm \times 25mm standard side rail, round angle anti-collision design;
- 6、 **Gas outlets configuration:** O₂*2, VAC*2, AIR*2, it also can be designed with your

requirements.

a、 Different color and shapes of gas outlets is for distinction.

b、 Using cycle for more than 20,000 times.

C、 Terminal flexible tube is PVC material, each pipe with different colors.

7、 Network interface:1 pc RJ45, the socket can be extended.

8、 The main body adopts 6063 high-strength aluminum alloy, no sharp corners on the surface and no screws exposed.

9、 The material surface treatment adopts electrostatic spraying, matt treatment, anti-corrosion, easy to clean and disinfect.

10、 Ceiling mounted which is more stable and firm.

二、 Configuration

No	Accessories Name	qty	unit
1	Oxygen	2	pc
2	VAC	2	pc
3	Air	2	pc
4	Power Socket	7	pc
5	Network Interface	1	pc
6	Instrument Platform	2	pc
7	Drawer	1	pc
8	Earth Terminal	1	pc
9	IV Pole with four hooks (Stainless steel material)	1	set
10	Syringe Pump Rack (Stainless steel material)	1	set
11	Pipe Management Tools	2	sets