

Security Alarm Cable

Specification

1)Conductor: (2-8cores are available)

Bare Copper/CCA Stranded or Solid Conductor

Flexible section in 0.8sqmm,1.0mm 1.5mm,ect

2)Insulation: PVC flame retardant/PE

3)Drain wire: (Options) In Stranded or Solid Bare Copper,CCA,CCS

4)Shielding: (Options) Aluminum/Polyester Foil Coverage

5)Outer Jacket: General PVC,PVC flame retardant,LSZH Sheath,Polyethylene Sheath

6)Color:Red White gray,ect

Item No.	Decription	Conductor Spec.	Insulation		Jacket		Packing
			Nom.Thick (mm)	Nom.Diam (mm)	Nom.Thick (mm)	Nom.Diam. (mm)	
ALARM	TC/BC/CCA/TCCA Screened Unscreened Rip cord or No Drain wire or No	2*7*0.2	0.22	1.05	0.45	3.1	Box Coil Drum Paper reel Plastic reel Wooden reel
		4*7*0.2	0.22	1.05	0.45	3.4	
		6*7*0.2	0.22	1.05	0.5	4.1	
		8*7*0.2	0.22	1.05	0.5	4.5	
		10*7*0.2	0.22	1.05	0.6	5.1	
		12*7*0.2	0.22	1.05	0.6	5.5	
		14*7*0.2	0.22	1.05	0.7	6.1	
		16*7*0.2	0.22	1.05	0.7	6.4	
		20*7*0.2	0.22	1.05	0.8	7.2	

