

Model NO.	MF2404	MF2404(Type-C)	MD2404	MD2404(Type-C)	MQ2404	MQ2404(Type-C)
Pictures						
Panel size	23.8"	23.8"	23.8"	23.8"	23.8"	23.8"
Panel type	TFT-LCD	TFT-LCD	TFT-LCD	TFT-LCD	TFT-LCD	TFT-LCD
Panel technology	IPS	IPS	IPS	IPS	IPS	IPS
Visibal area	527.04×296.46	527.04×296.46	527.04×296.46	527.04×296.46	527.04×296.46	527.04×296.46
View angle	178° (H) / 178° (V)	178° (H) / 178° (V)	178° (H) / 178° (V)	178° (H) / 178° (V)	178° (H) / 178° (V)	178° (H) / 178° (V)
Max. Resolution	1920*1080	1920*1080	1920*1080	1920*1080	2560*1440	2560*1440
Aspect Ratio (H:V)	16: 9	16: 9	16: 9	16: 9	16: 9	16: 9
Refresh rate(Hz)	75Hz	75Hz	165Hz	165Hz	75Hz	75Hz
Brightness	250 cd/m ² ±20	250 cd/m ² ±20	250 cd/m ² ±20	250 cd/m ² ±20	250 cd/m ² ±20	250 cd/m ² ±20
Surface treatment	matte	matte	matte	matte	matte	matte
Contrast Ratio	1000:1 (Typ.)	1000:1 (Typ.)	1000:1 (Typ.)	1000:1 (Typ.)	1000:1 (Typ.)	1000:1 (Typ.)
Color quantity	16.7M (8-bit)	16.7M (8-bit)	16.7M (8-bit)	16.7M (8-bit)	16.7M (8-bit)	16.7M (8-bit)
Color gamut	97% sRGB	97% sRGB	97% sRGB	97% sRGB	97% sRGB	97% sRGB
Display mode	black	black	black	black	black	black
Response time	5ms (+OD)	5ms (+OD)	1ms (+OD)	1ms (+OD)	5ms (+OD)	5ms (+OD)
Input/Output interface						
HDMI input	x 1	x 1	x 1	x 1	x 1	x 1
VGA input	x 1	x 1	x 0	x 0	x 0	x 0
DP input	x 0	x 0	x 1	x 1	x 1	x 1
Type-C	x 0	x 1	x 0	x 1	x 0	x 1
Headphone Output	x 0	x 1	x 1	x 1	x 1	x 1
USB	x 0	x 0	x 1	x 0	x 1	x 0
Other Features						
Support G-Sync(Free-sync)	/	support	support	support	support	support
Game plus	/	support	support	support	support	support
HDR function	/	support	support	support	support	support
Reduce BLU-RAY Mode	support	support	support	support	support	support
curvature	Flat	Flat	Flat	Flat	Flat	Flat
RGB BACKLIGHT EFFECT	/	/	/	/	/	/
Built-in speaker	/	optional	/	optional	/	optional
VESA	100*100	100*100	100*100	100*100	100*100	100*100
Power						
Power supply mode	external power supply	external power supply	external power supply	external power supply	external power supply	external power supply
AC input	100-240V,50/60Hz,0.8A	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A
DC input	12V-2.5A	12V-3A	12V-3A	12V-3A	12V-3A	12V-3A
Power Consumption	< 30W	< 36W	< 36W	< 36W	< 36W	< 36W
Stand by Mode	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W
Off Mode	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W
Accessory						
HDMI signal line	x 1	x 1	x 0	x 0	x 0	x 0
DVIsignal line	x 0	x 0	x 0	x 0	x 0	x 0
VGA signal line	x 0	x 0	x 0	x 0	x 0	x 0
DP signal line	x 0	x 0	x 1	x 1	x 1	x 1
Type-C signal line	x 0	x 1	x 0	x 1	x 0	x 1
Power line	x 1	x 1	x 1	x 1	x 1	x 1
Audio line	x 0	x 0	x 0	x 0	x 0	x 0
power adapter	x 1	x 1	x 1	x 1	x 1	x 1
Manual	x 1	x 1	x 1	x 1	x 1	x 1
Qualified Certificate	x 1	x 1	x 1	x 1	x 1	x 1
Bracket	x 1	x 1	x 1	x 1	x 1	x 1
stand base	x 1	x 1	x 1	x 1	x 1	x 1
screw	x 1	x 1	x 1	x 1	x 1	x 1
Packing						
Carton dimension (L*W*H)	595*125*380	595*125*380	595*125*380	595*125*380	595*125*380	595*125*380
Gross weight	4.45	4.45	4.45	4.45	4.45	4.45
Net weight	2.85	2.85	2.85	2.85	2.85	2.85