



深圳市星光彩科技有限公司


Shenzhen Xing Guang Cai Technology Co., Limited

Add: 2505 Songbai Road, Shiyan Town, Baoan District, Shenzhen, China

Web: www.xgclcd.com

P4 Outdoor full color led display parameter

LED Module



pixel pitch	4mm
module size	256*128mm
module resolution	64*32
LED	SMD1921
Scan	1/8scan
Application	Outdoor
Weight	0.4KG
Chips	Epistar

LED Cabinet



Cabinet Size	1024mm(L)*768mm(H)
Cabinet resolution	256*192dots
module quantity	4*6pcs
Power supply quantity	8PC G-Energy 5V 40A 200W
Material	Iron
Receiving card quantity	2PC
Thickness	About 18cm
Weight	30KG

LED Screen



2016-11-29 16:47

<https://szxgclcd.en.alibaba.com/>

Pixel	62500dots/m²	Continuous Working Hours	>72 hours
Ave power consumption	600W/m²	Using Life	100,000 hours
Max power consumption	1500W/m²	MTBF	>10,000H
Optimum Viewing Distance(m)	≥4m	Scatter OOC Point	<0.01%
Brightness(cd/m ²)	≥4000cd	Continuous OOC Point	None
Refresh Rate	300---2440 frame/s	IP Grade	IP65/IP54
LED Drive mode	Constant Current	Working Temperature	-35C----+60C
Display color	17M---69G	Working Humidity	10---90%



深圳市星光彩科技有限公司 Shenzhen Xing Guang Cai Technology Co., Limited

4.Regular package:



5.Certifications: CE ROS FCC CCC

