



T80

INTERNET OF THINGS HANDHELD TERMINAL

4.5-inch HD screen · Quad -core · 4G full Netcom



Android



4G



WIFI



Bluetooth



1D barcode



2D barcode



NFC



Camera



GPS



Product parameters

Performance

CPU	Cortex-A53 Quad-core 64-bit 2.0GHz high-performance processor
RAM+ROM	2GB+16GB Supports up to 3GB+32GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 8.1/Android 9.0

Data communication

WLAN	Dual-band 2.4GHz/5GHz Supporting IEEE 802.11ac/a/b/g/n/d/e/h/i/j/k/r/v protocol
WWAN	2G: GSM(850/900/1800/1900MHz)
	3G: WCDMA(850/900/1900/2100MHz)
	4G: FDD(B1/B3/B4/B7/B8/B12/B20) TDD(B38/B39/B40/B41)
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters
GNSS	Support GPS, Galileo, Glonass, Beidou

Physical parameter

Dimensions	166mm x77.5mm x22mm
Weight	< 500g (Depends on device function configuration)
Display	4.5 inch display with resolution 480 x854
TP	Supports multi-touch
Battery capacity	Rechargeable polymer battery 3.8V 4200mAh, removable
	Standby time > 350 hours
	Working time > 12 hours, Depending on usage and network environment
	Charging time 2-3 hours, Using standard power adapter and data cable
Camera	Rear camera: 8MP Support auto focus, Flash, etc.
Expansion Card slot	Micro SIM card x1, TF card x1
Communication interface	Type-C USB x1, Support OTG function
Audio	Speaker (mono), Microphone, Receiver
Keypad	Support touch screen soft keypad and physical keypad
Sensors	Gravity sensor, Vibration motor

Language/input method

Input	English, Pinyin, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, etc.

Data collection

Barcode scanning (Optional)

1D Scanning engine	Mindeo 966, Honeywell N4313
1D Symbolgies	Code128, EAN-13, EAN-8,Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, China post 25, ISBN/ISSN,Code93, UCC/EAN-128, GS1Databar,HIBC, etc.
2D Scanning engine	N6602, Honeywell N5703 N6703
2D Symbolgies	PDF417, Micro PDF417, GS1 Composite, Aztec Code, Data Matrix, QR Code, Micro QR Code, Maxicode, Hanxin Code, etc.

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 protocol
Distance	2cm-5cm

User environment

Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH - 95%RH(no condensation)
Drop specification	6 sides Supports 1.5 meters drops on the marble within the operating temperature
Rolling test	0.5m rolling for 6 sides, can still work steadily
Sealing	IP66

Accessories

Standard	Adapter x1, Data cable x1, Protective film x1, Instruction manual x1
Optional	Charging base, etc.

Special Note: Product data is for reference only and subject to change without notice. model: T80 Update: 2023-10-31



Company : Blovedream Technology Co., Ltd.
Official website: www.lckj.cn | www.blovedream.net National hotline: 15090996352
Address: 4th Floor, Building A, Phoenix Zhigu Building, Country Garden, Xixiang, Baoan District, Shenzhen